

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 100540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 7; & 12 of T25-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W. H. Byars, Contract #272 dated August, 1877
(DCSO records, Volume 9 Page 3848)

Set a Maple post 40" long, 3" dia. for ¼ sec. cor., from which
A Cedar, 16" dia. bears N.83°E., 70 lks. dist.
A Fir, 50" dia. bears N.55°W., 94 lks. dist.

Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy; Mike
Stone - July, 1963 - C.S. File 49/123-91

Found - 50" Fir stump N.55°W., 62.0 ft., old & badly charred
and rotten. Two old axe faces on bark, scribe
mark upper half of "S".
Cedar, down & half-burned away, N.83°E., 456.2 ft.
No marks found.

Set brass cap at cor. mkd: County Surveyors Office, 1963
T25S R7W ¼ S12|S7 R6W

New BTs - 15" D.Fir N.55°E., 24.8 ft. mkd: ¼ S 7 CS BT.
10" D.Fir N.2°W., 19.2 ft. mkd: ¼ S12 CS BT.

(A 27" I.Cedar with Grant & Evans' yellow tag bears N.70°E.,
100.6 ft., formerly used as NE BT.)

Cor. lies on very steep & rocky north slope, approx. 50 ft.
south of small draw sloping East, at foot of slope.

FD. OK - David Edwards - Feb. 1997 - M 126-45 & CS 65/12-3A&B