

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7; & 1 & 12, T25-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - W.H. Byars, Contract #272, dated August, 1877  
(DCSO records, Volume 9 Page 3849)

-----  
Set a Cedar post, 40" long, 4" dia. 1/3 in ground, for the  
cor. to secs. 1, 6, 7 and 12, from which  
A Fir 18" dia. bears N.60°E., 5 lks. dist.  
A Fir 36" dia. bears S.2°E., 26 lks. dist.  
A Fir 36" dia. bears S.2°W., 18 lks. dist.  
A Fir 16" dia. bears N.40°W., 5 lks. dist.

-----  
Wm. P. Heyden, Contract #656, dated May 21, 1896. (DCSO  
records Volume 9 Page 3851)

-----  
At the cor. of secs., 1, 6, 7 and 12, T.25S Rs 6 & 7W., which  
is a post, marked & witnessed as described by the Surveyor  
General. The post being badly decayed in its place, I set a  
new Fir post, 4 ft. long, 5" sq., 36" in the ground marked  
T 25 S S 6 on the NE., R 6 W S 7 on SE., R 7 W S 12 on SW. &  
S 1 on NW. faces, with 5 notches on S. and 1 notch on N.  
edges.  
The original witness trees being in good condition, I make no  
change.

-----  
Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy; Mike  
Stone - July 1963 - C.S. File 49/123-92

-----  
Found - 38" Fir S.2°W., 11.9 ft. Faint bark scribing visible  
"12 T26 7W". Axe marks visible at location for  
BT.  
36" Fir S.2°E., 17.2 ft. old axe marks visible on  
bark (2 scars), no scribing.  
24" Fir N.40°W., 3.3 ft. illegible scribe marks  
visible on bark.  
24" Fir N.60°E., 3.3 ft. Good axe scar visible. Did  
not open. (distances are all from face of tree)  
Set brass cap at cor. mkd: County Surveyor T25S R7W S1|S6 R6W  
Office, 1963 S12|S7

Blaze & rescribed:

24" D.Fir N.55°E., 4.2 ft. mkd: T25S R6W S6 CS BT.  
36" D.Fir S.5°E., 19.0 ft. mkd: T25S R6W S7 CS BT.  
24" D.Fir N.38°W., 4.5 ft. mkd: T25S R7W S1 CS BT.  
New BT - 16" D./Fir S.22°W., 21.8 ft. mkd: T25S R7W S12 CSBT.  
Corner lies on gentle west slope approx. 80 ft. W. of top of  
ridge.

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7; & 1 & 12 of T25-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Bruce Shaner Engineering - For: Western Timber Company  
July 28, 1989 - C.S. File 63/96 and RM 3-72

-----  
CORNER REPORT ONLY

Found - 1" I.P. with 2½" brass cap, (County, 1963)  
38" D.Fir now a snag 10 ft high bears S.2°W. 11.9 ft  
24" D.Fir now a 6 ft. high stump, face overgrown,  
bears N.55°E., 4.2 ft.  
36" D.Fir now a 6 ft. high stump, face overgrown  
bears S.5°E., 19.0 ft.  
24" D.Fir now snag face overgrown bears N.38°W. 4.5 ft  
16" D.Fir now a 10 ft. high snag, face burnt off,  
bears S.22°W., 21.8 ft.  
Corner lies on a gentle west slope, approx. 80 ft. west of  
dirt road along summit of Tye Mt.

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike  
- 10/24/2007 - C.S. File 67/24-35

-----  
Found - 2½" dia., brass cap, properly mkd., on 1¼" O.D. iron  
pipe. Projects 12" above ground, firmly set.  
Steel fence post fd. to NE approx. 6" away.  
38" now 37" dia., x 9 ft. tall D.Fir stump partial  
bark scribe "6" visible bears S.2°W., 13.4 ft.,  
11.9 ft. to face (1963 rec. S.2°W., 11.9 ft. to  
face of tree) OBT  
36" now 36" dia., x 8 ft. tall D.Fir stump, rotted  
blaze, bears S.5°E., 19.0 ft. Note: Stump is  
pistol butt. (Agrees w/rec.) OBT  
24" now 24" dia., x 10 ft tall D.Fir snag, partially  
healed blaze shows illegible scribe bears  
N.55°E., 4.2 ft. (agrees w/1963 rec.) OBT  
24" now 24" dia., x 6 ft tall D.Fir stump, burnt  
face w/burling visible bears N.38°W., 4.5 ft.  
(agrees w/1963 rec) OBT  
16" now 12" dia. x 8 ft tall D.Fir stump, face burnt  
off bears S.22°W. 21.8 ft (agrees w/rec) 1963 BT  
Set - 6" dia., D.Fir double blazed & scribed "T25S R6W S7  
CS BT" bears S.16½°E., 9.7 ft.  
7" dia., D.Fir double blazed & scribed "T25S R7W S1  
CS BT" bears N.84°W., 10.0 ft.  
5" dia., D.Fir double blazed & scribed "X" on high  
blaze & "CS BT" bears N.25½°E., 9.8 ft.  
Note - Compass decl. 16¼°E.