

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION Tsp. Cor. (NW Cor. Sec. 6)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853
(DCSO records, Volume 8 Page 3130)

Set post cor. to Tps. 24 & 25 South & bet. Rgs. 6 & 7,
from which:

- A Fir 36" dia. bears S.80½°W., 89 lks. dist.
- A Fir 30" dia. bears N.7½°W., 122 lks. dist.
- A Fir 28" dia. bears N.56 3/4°E., 97 lks. dist.
- A Fir 44" dia. bears S.18°E., 70 lks. dist.

BLM resurvey by Lynn Roseberry, under Group #645, Survey
Aug./Sept. 1967 (DCSO records, Vol. 36 Page 14941)

Point for the cor. of tps. 24 and 25 S., R. 6 W., at record
distance in latitude from the corner of secs. 30 and 31 only
on the west boundary of T.24S R.6W.; and at record distance
in departure from the cor. of secs. 5, 6, 31 and 32; there
is no remaining evidence of the original corner.

Set a Iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the
ground, with brass cap mkd:

| | | |
|--------|--------|--------|
| | | T 24 S |
| | | R 6 W |
| T 25 S | S | 31 |
| R 7 W | S | 6 |
| S 1 | T 25 S | |
| | | 1967 |

from which

- A Fir 14" dia. bears N.20¼°E. 83 lks mkd T24S R6W S31 BT
- A Fir 10" dia. bears S.57°E., 26 lks mkd T25S R6W S6 BT.

DCSO-GIS Corner visitation - 5/12/2004 - Typed: 1/21/2011 -
C.S. File 67/33-1

Monument - 2" IP/BC
Comment - OK