

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853
(DCSO records, Volume 6 Page 3843)

Set ¼ sec. post, from which
 A Y.Oak 30" dia. bears S.76½°W., 90 lks. dist.
 A Y.Oak 26" dia. bears N.88½°E., 130 lks. dist.

Glenn Baughman, For: John Tilley, May 1978 - M 70-18

Found - Orig. 26" Oak, now 56", bears N.88°30'E., 87.0 ft.
 scribes visible.
 Orig. 30" Oak, down, bears S.76°30'W., 59.4 ft. to
 root hole.
Set - Brass cap.
New BTs - 9" D.Fir bears N.12°W., 27.7 ft. scribed ¼ S18 BT.
 10" D.Fir bears S.83°E., 12.6 ft. scribed ¼ S19 BT.

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J.
Flause - 2/26/1998 - C.S. File 64/79-37

Found - 2½" dia., brass cap on a 1½" O.D. iron pipe,
 protrudes 6" above ground. 1978
 26" now 46" dia., B.Oak with a previously opened
 partially healed blaze, no scribing visible,
 bears S.89½°E., 89.8 ft. to center of trunk
 (1978 rec. N.88½°E., 87.0 ft.) OBT
 Orig. SW BT not found.
 10" now 13" dia., D.Fir with a partially healed
 burnt single blaze, illegible scribing
 visible, bears S.74°E., 12.6 ft. (Rec.
 S.83°E., 12.6 ft.) 1978
 9" now 10" dia., 4 ft. high D.Fir stump with a
 partially healed burnt single blaze,
 illegible scribing visible, bears N.9°E.,
 27.7 ft. (Rec. N.12°W., 27.7 ft.) 1978
New BTs- 20" dia., D.Fir, double blazed and scribed "¼ S18
 CS BT" bears N.22½°E., 25.8 ft.
 16" dia., D.Fir, double blazed and scribed "¼ S18
 CS BT" bears N.46°W., 35.7 ft.
Note - Renewed position of corner as determined by 1978
 renewal. Corner lies at the intersection of
 fences running South and West. 37' West,
 fence runs North.

Fd. BC & BTs 1/2025 - by N. Hibbs M185-26