

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 7 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder & Gile, Contract #31 dated April, 1853  
(DCSO records, Volume 9 Page 3850)

-----  
Set a Dogwood post, 40" long, 16" in the ground, from which  
A Fir, 40" dia. bears N.27°W., 18 lks. dist.  
A Fir, 60" dia. bears S.5°W., 33 lks. dist.

Douglas Co. Surveyors Office - James W. Byron; Milo Godfrey;  
S.A. Bilow; November 12, 1958 - C.S. File 49/123-93

-----  
Found - Orig. 40" now 48" Fir stump N.27°W., 11.9 ft. Tree  
cut 10 ft. down hill, shows good bark scribing  
"¼ S".

Orig. 60" now 66" Fir S.5°W., 21.8 ft. shows faint  
bark scribe "¼ S".

Set brass cap at cor. mkd: ¼  $\frac{S\ 7}{S18}$  T25S R6W County Surveyor's  
Office, 1958

(Sketch in file showing relationship to fences)

New BTs - 66" W.Fir S.5°W., 24.3 ft. scribed ¼ S18 CS BT.  
Bark scribed.

7" W.Fir N.7°E., 4.8 ft. scribed ¼ S 7 CS BT.

Milo E. Godfrey, Dep. Co. Surveyor; Vernon Tracy; Mike Stone  
July, 1963 - C.S. File 49/123

-----  
Found - DCSO brass cap, 1958, in E. & W. fence line.  
66" Fir, S.5°W., 24.3 ft. Tree now dead, bark badly  
burned. No scribing.

7" W.Fir stump N & E, 4.8 ft. Bottom of axe face  
near top of stump, no scribing.

48" Fir stump N.27°W., 11.9 ft. Stump badly burned,  
no scribing visible.

Blaze & Rescribed:

66" Fir snag (in wood) S.5°W., 24.3 ft. mkd. ¼  
S18 CS BT.

Blaze & Scribe:

24" Fir snag 15 ft. high, N.81°E., 127.2 ft. mkd.  
¼ S 7 CS BT.

No live trees left within reasonable distance of corner.

Fd. BC & BTs 1/2025 - by N. Hibbs M185-26