

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Sec Cor for 19, 20, 29 & 30

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Elder & Gile, Contract #31 dated April, 1853
(DCSO records, Volume 9 Page 3841)

Set post cor. to secs. 19, 20, 29 and 30, from which
A W.Oak 13" dia. bears S.83¾°E., 486 lks. dist.
A W.Oak 24" dia. bears N.17½°E., 296 lks. dist.
A Y.Oak 16" dia. bears N.85¼°W., 301 lks. dist.
A Y.Oak 11" dia. bears S.61¾°W., 300 lks. dist.

Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy; Mike
Stone - August, 1962 - C.S. File 49/123-25

Found - Rotten shell, remains of Oak tree, N.85¼°W.,
198.7 ft. Faint reverse scribing visible on
inside. "W" "S" "9" & "B" legible.
W.Oak now 36", N.12½°E., (instead of N.17½°E.)
195.4 ft. Two good scars plainly visible.
B.Oak nearly dead, S.61¾°W., 203.0 ft. (instead of
198.0 ft.) Now 28" dia. Did not open.
W.Oak now 24", S.87°E., (instead of S.83¾°E.) 320.8
ft. Faint scar visible. Blaze & rescribe this
tree: "T25S R6W S29 CS BT".

Set brass cap at cor. mkd: County Surveyor's T25S R6W S19|S20
Office, 1962 S30|S29

New BTs - 9" W.Oak N.36°W., 65.0 ft. mkd: T25SR6W S19 CS BT.
8" W.Oak S.75°W., 147.1 ft. mkd: T25SR6W S30 CS BT.
24" B.Oak N.47°E., 156.0 ft. mkd: T25SR6W S20 CS BT.

Corner falls in fence corner, fences North, South & East from
corner. This location satisfies more calls than any other, 3
distances & 2 bearings to original trees. Note: all distances
from old BTs measured from face of trees.

Fd. Ok by Carl Sweeden, - Aug. 1998 - M130-22.

DCSO-GIS Corner visitation - 7/6/2004 - Typed: 1/24/2011 -
C.S. File 67/33-1

Monument - 1.25" BC/IP
Comment - OK

Fd. as per rec. 12/2024 N Hibbs M185-20