

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853
(DCSO records, Volume 9 Page 3845)

Set ¼ sec. post (on top of ridge, course N.70°W., and
S.70°E.), from which

A Y.Oak 14" dia. bears N.55°E., 74 lks. dist.

A W.Oak 9" dia. bears S.70°W., 87 lks. dist.

M.B. Germond, Dep. Co. Surveyor - For: Cal Durling
March 17, 1909 - Volume 2 Page 157

Set W.Oak post 4" x 4" x 8 ft., from which

R.Fir 8" dia. bears N.52°00'E., 16 lks.

R.Fir 50" dia. bears N.60°00'W., 27 lks.

Found one old BT standing.

James W. Byron; Milo E. Godfrey; S.A. Bilow - November 12,
1958 - C.S. File 49/123-32

Found - Germond's 50" Fir, now 61", N.60°W., 17.8 ft. good
blaze, no scribing found.

Completely rotted stump N.52°E., 10.6 ft. pitched
over sliver from face of this tree scribed
"¼S8 BT" was stuck in fence beside remnant of
old stump.

Part of old squared Oak post (no scribing visible)
lying on ground alongside of corner.

Set brass cap at cor. mkd: ¼ S7|S8 T25S R6W County Surveyor's
Office, 1958

New BTs - 13" D.Fir N.86°E., 10.7 ft. "¼ S8 CS BT".

11" D.Fir N.30°W., 32.8 ft. "¼ S7 CS BT".

Cor. lies in fence cor. - fences E.-N. & S. & directly on top
of ridge.

All BTs burned and dead - Oct. 16, 1962 - M.E.G.- C.S. File
49/123-34

Fd. BC by D. Edwards, 7/2007 - M154-1

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike
- Kody Inda - 9/12/2007 - C.S. File 67/24-18

Found - 2½" dia., brass cap properly mkd, firmly set,
projects 16" above ground. Noted brass cap is
situated approx. N.45°W.

61" dia., now a shattered rotted 10 ft tall fir
stump no marks visible, bears N.60°W., 17.8 ft.
(agrees w/rec.) 1909 BT cont. next page

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

New - Both 1958 BTs now gone.
8" dia., D.Fir double blazed & scribed "¼ S7 CS BT" bears S.45°W., 15.4 ft.
Most southerly trunk of triple trunk B.Oak is 8" dia., double blazed & scribed "¼ S7 CS BT" center of root crown bears N.40°W., 54.7 ft.
11" dia., madrone, double blazed & scribed "¼ S8 CS BT" bears N.22¾°E., 33.3 ft.
Most northerly trunk of triple trunk madrone is 8" dia., double blazed & scribed "¼ S8 CS BT" center of root crown bears S.27°E., 37.4 ft.
Note - Fences extend North, south and east from corner.
Compass decl. 16¼°E.