

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post cor. to secs. 5, 6, 7, & 8, from which
A Laurel 13" dia. bears S.25°W., 55 lks. dist.
A W.Oak 6" dia. bears S.32½°E., 76 lks. dist.
A W.Oak 7" dia. bears N.65¼°E., 145 lks. dist.
A Y.Oak 11" dia. bears N.5°W., 55 lks. dist.

Surveyor (?) (Possibly Germond) Date (?) Volume 2 Page 265

Set W.Oak post 4" x 4" x 3 ft. from which
R.Fir 8" bears N.49°40'E., 31 lks.
W.Oak 6" bears N.23°45'W., 48 lks.
R.Fir 5" bears S.53°40'E., 4 lks.
R.Fir 3" bears S.28°30'W., 25 lks.
Old BT in evidence.

C.W. Springer, Surveyor; C.A. Beeman; For M.F. DeCosta;
R. Lehman; J.A. Cole; Guy Cole, interested parties.
June 25, 1923 - Volume 3 Page 159 and Field Book 52 Pg. 11

I re-establish from 3 witness trees mkd. by Germond, only one of which alive & standing, other 2 are dead stumps now. The 4th no trace of. I drove an Oak stake 3 x 3 x 36 in ground and re-mark trees as follows:
12" Fir N.52°E., 20.5 ft.
48" Fir S.16°E., 340 ft.
10" Chincapin S.8°30'W., 232.2 ft.
6" Oak grub N.71°W., 253.6 ft.
Also set an oak stake 4 x 4 x 36 in ground.

Milo E. Godfrey, Deputy Co. Surveyor - V. Tracy; Mike Stone
November, 1958 - C.S. File 49/123-31

Found - No orig. BTs. Germond's & Springer's, now 26" R. Fir N.49°40'E., 20.5 ft. shows scars. I do not open.
Springer's 48" now 54" Fir S.16°E., 34.0 ft. Open & find good scribing.
Also find Springer's 6" now 14" W.Oak N.71°W., 253.6 ft. shows faint scar. I do not open.

(Continued Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>Set brass cap mkd: County Surveyor's $\begin{matrix} S 6 & & S 5 \\ S 7 & & S 8 \end{matrix}$ T25S R6W Office 1958</p> <p>New BTs - 7" B.Oak bears N.83°W., 20.0 ft. scribed T25S R6W S 6 CS BT. 6" R.Fir bears S.34°E., 58.5 ft. scribed S 8 CS BT. 14" R.Fir bears S.64°W., 79.6 ft. scribed S7 T25S R5W.</p>
<p>M. Godfrey, Deputy - M. Stone - Oct. 11, 1962, C.S. 49/123-31 -----</p> <p>Found - B.C. set in 1958. 7" B.Oak N.83°W., 20.0 ft. Tree alive. All other trees found or scribed in 1958 dead & down.</p> <p>New BTs - 4" D.Fir N.33°E., 44.2 ft. mkd: S5 CS BT. 10" D.Fir S.83°E., 65.5 ft. mkd: T25S R6W S8 CS BT 8" B.Oak S.37½°W., 57.2 ft. mkd: T25S R6W S7 CS BT.</p>
<p>Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 5/5/94 - C.S. File 64/51-5 -----</p> <p>Found - 2½" dia., brass cap on a 1½" O.D. iron pipe protruding 11" above ground. (1958) (Note marks on cap face southeast) 7" now 26" dia., 2' high Oak stump with a fully healed lower blaze bears N.83°W., 20.0' (Agrees with rec.) 1958 4" now 13" dia., D.Fir with a fully healed double blaze, bears N.31°E., 44.2' (Rec. N.33°E., 44.2') 1962 10" now 27" dia., 8" high D.Fir stump with a fully healed lower blaze, bears S.85°E., 65.0' (Rec. S.83°E., 65.5') 1962 8" now 14" dia., W.Oak with a fully healed double blaze bears S.36°W., 57.2' (Rec. B.Oak S.37½°W., 57.2') 1962</p> <p>New BTs - 5" dia., D.Fir double blazed and scribed "T25S R6W S8 CS BT" bears S.78°E., 22.2'. 7" dia., W.Oak double blazed and scribed "T25S R6W S8 CS BT" bears 25.3'.</p> <p>Note - Corner lies at the intersection of a four way fence corner. See C.S. File for sketch.</p>
<p>continued next page</p>

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor. Secs. 5, 6, 7, & 8

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

DCS0-GIS Corner visitation - 7/6/2004 - Typed: 1/24/2011 -
C.S. File 67/33-1

Monument - 1.25" BC/IP
Comment - OK