

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Sec cor for 5, 6, & 31, 32, T24-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder & Gile, Contract #31 dated April, 1853 (DCSO records, Volume 8, Page 3133)

Set post cor. to secs. 31, 32, 5 & 5, from which
A Fir 6" dia. bears N.32½°E., 54 lks. dist.
A Fir 14" dia. bears N.13°W., 58 lks. dist.
A Y.Oak 12" dia. bears S.74°W., 136 lks. dist.
A Fir 15" dia. bears S.6°E., 155 lks. dist.

Ben B. Irving, County Surveyor - Ned Dixon, Witness -
December 31, 1947 - C.S. File 38/230

Location identified by two O.B.T.'s original scribe marks still legible but trees down and rotting.
Oak bearing S.74°W., 136 lks.
Fir bearing N.13°W., 58 lks.
Set a 4" x 4" x 48" Cedar post 15" in the ground for corner.
Marked New BTs:
14" Fir bears N.75°E., 28.0 ft.
18" Fir bears N.1°W., 60.0 ft.
22" Fir bears S.4°W., 64.6 ft.
16" Fir bears S.37°E., 68.0 ft.

Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy; M. Stone
November 1962 - C.S. File 49/123-51

Found - Scribed cedar stake.
19" Fir snag N.75°E., 28.0 ft. good bark scribing, plainly visible, "T24S R6W S32 CS BT".
18" Fir S.37°E., 68.0 ft. shows 2 very plain axe scars, trees nearly dead.
21" Fir S.6°W., (not S.4°W.) 64.6 ft. to face, shows 2 very plain axe scars, tree alive & in good condition.
Fir stump N.1°W., 60.0 ft. shows good axe scar.
Set brass cap at cor. mkd: County Surveyor's S31|S32 T24S
Office 1962 S 6|S 5 T25S R6W
Drive scribed cedar stake alongside.
New BTs- 21" D.Fir S.77°E., 53.4 ft. mkd. T25SR6W S5 CS BT.
31" D.Fir N.66°W., 53.8 ft. mkd. T24SR6W S31 CS BT.
7" D.Fir N.20°E., 117.3 ft. mkd. T24SR6W S32 CS BT.
Fence cor., fences N., S. & E., bears N.60°W., 23 ft.

Fd. & Used, BLM Dependent Resurvey, 1967 - Fd. B.C. and 10
BTs. (DCSO records, Volume 36, Page 14939-40)

continued next page

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Sec cor for 5, 6, & 31, 32, T24-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Mark Smalley - For Roseburg Forest Prod. - 9/21/93 - C.S.
63/153-37

Found - Douglas County Surveyor's BCIP
 Fir, 30"dia., N.66°W., 53.8 ft., visible scribe
 Fir, 24"dia., S.37°E., 64.0 ft., healed face
 Fir, 28"dia., S.77°E., 53.4 ft., healed face
New Accessories -
 Fir, 10"dia., S.55°W., 40.4 ft., scribed "S6 BT"

Fd. ok by Mark Smalley - June 1998 - M 128-73