TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853 (DCSO records, Volume 9 Page 3839)

Set ¼ sec. post, from which
A W.Oak 22" dia. bears N.85°E., 513 lks. dist.
A W.Oak 24" dia. bears S.78°E., 462 lks. dist.
N.66½°W., to a house, S.18½°W. to Barrett's house.

Milo E. Godfrey, Dep. Co. Surveyor - Vernon Tracy; Mike Stone January 1963 - C.S. File 49/123-71

Found - 46" W.Oak S.78°E., 305 ft. Cut open & found good scribing "B", part of "T".
Old rotten Oak stump, cut low, N.85°E., 338.6 ft. Cut low to found scribing.
Set brass cap at cor. mkd: County Surveyors Office, 1963 T25S R6W ¼ S29/S32
New BTs - 20" B.Oak S.10½°W., 133.9 ft. mkd: ¼ S32 CS BT.
14" W.Oak N.76°E., 213.3 ft. mkd: ¼ S29 CS BT.

Fd. Brass Cap - M. Heimburger, Oct. 1991 - M 112-35

Douglas County Surveyors Office - Randall Smith & Stephen Flause - June 26, 97 - C.S. 64/75-13

Found - 2½" Brass cap on a 1½" iron pipe protrudes 9" above ground.
24" now 48" W.Oak, with a partially healed previously opened blaze bears S.78°E., 305'", (agrees with rec.) OBT.
22" W.Oak now rotted remains of an oak stump, bears N.85°E., 338.6' (agrees with rec.) OBT.
20" now 26" dia. B.Oak, with a fully healed double blaze, bears S.10½°W., 133.9' (agrees with rec.) 1963.
14" now 25" dia. W.Oak, with a fully healed blaze, bears N.76°E., 213.3' (agrees with rec.) 1963
New - 26" dia. Ash, double blazed and scribed "¼ S32 CS BT", bears S.40°E., 23.5'.
14" dia. Ash, double blazed and scribed "¼ S29 CS BT", bears N.36°W., 15.9'.

DCSO-GIS Corner visitation - 7/6/2004 - Typed: 1/24/2011 - C.S. File 67/33-1

Monument - 1.25" BC/IP
Comment - OK