TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853
(DCSO records, Volume 9 Page 3841)

Set ¼ sec. post, from which
A W.Oak 30" dia. bears N.30°E., 902 lks. dist.
A Y.Oak 48" dia. bears N.3°W., 1254 lks. dist.
No tree near S. of line

Milo E. Godfrey, Dep. Co. Surveyor - Vernon Tracy; M. Stone
January 1963 - C.S. File 49/123-69

Found - W.Oak now 50", N.30°E., 595.3 ft. previously opened found reverse scribing.
Rotted remnants of very large Oak stump, in place, approx. 750 ft. N. of cor. Old axe marks on one fragment of wood. This does not check for bearing & distance from corner, but I believe it was other old BT.
Set brass cap (from NE BT) mkd: County Surveyors Office 1963
T25S R6W ¼ S20/S29
New BTs - 16" B.Oak N.32°W., 19.6 ft. mkd: ¼ S20 CS BT.
12" W.Oak S.49°E., 12.5 ft. mkd: ¼ S29 CS BT.
Corner position falls in bed of small stream.

Fd. Ok by Carl Sweeden, - Aug. 1998 - M130-22.
Fd. BC per rec. 4/2018, M Heimburger - M174-37

Fd. as per rec. 12/2024 N Hibbs M185-20