

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Original - Elder & Gile, Contract #31 dated April, 1853  
(DCSO records, Volume 9 Page 3843)

-----  
Set ¼ sec. post, from which  
A W.Oak 6" dia. bears S.9°W., 26 lks. dist.

G.G. Stewart, for: Henry Howard - January 25, 1923 -  
C.S. File 17/35

-----  
Found 20" BT and Oak stake.  
Drove stake, marked:  
14" Fir N.66°W., 29.0 ft.  
6" W.Oak S.9°W., 17.2 ft.

Milo E. Godfrey, Deputy - Mike Stone - October 15, 1962 -  
C.S. File 49/123-36

-----  
Found - 24" Fir stump N.66°W., 29.0 ft. Found bottom of old  
axe scar, but tree was cut off below all  
scribing.  
Stump hole & remnants of Oak tree S.9°W., 17.2 ft.  
Definite traces of old axe face, but no  
scribing left, most of face has rotted away.  
Stump hole & rotten remains of Oak stump N.45½°W.,  
58.1 ft. Too far gone to find any trace of  
scars or scribing.  
Set brass cap at cor. mkd: County Surveyor's T25S R6W ¼ S17  
Office, 1962 S20  
New BTs - 10" D.Fir S.59°E., 9.7 ft. mkd. ¼ S20 CS BT.  
9" D.Fir N.12°W., 44.3 ft. mkd. ¼ S17 CS BT.  
Corner lies 7 ft. South of a new E. & W. fence line.

Found OK, April 1981 - R. Dolan - M 87-39  
Found OK by Russ Dodge, Apr. 1996 - M125-1  
Fd. Ok by Carl Sweeden, - Aug. 1998 - M130-22.

Carl Sweeden - For: Fred Russell - Aug. 2001 - M138-61

-----  
Found - 2½" BC on 1¼" O.D. iron pipe up 0.85' 7.0' S. of E/W  
wire fence.  
24" D.Fir BT stump mostly rotted, ax marks on face,  
N.66°W., 29.0'.  
Evidence of depression perhaps stump hole of Oak BT,  
S.9°W., 17.2'.  
Evidence of depression perhaps stump hole of Oak BT,  
N.45½°W., 58.1'.  
continued next page

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>10" now 17" D.Fir BT, S.59°E., 9.7', scar visible, tag &amp; old fence wire in tree. 9" now 12" D.Fir BT stump, N.12°W., 44.3', face rotted - no trace of scribe marks. New BTs- 19" Madrone BT, S.83°E., 25.80' "N ¼ S20 BT" tagged. 12" D.Fir BT, N.44°W., 27.50' "S ¼ S17 BT" tagged. 12" W.Oak BT, N.7°W., 43.00' "S ¼ S17 BT" tagged.</p>