

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION 1/4 Corner, N. side Sec. 5

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Original - Elder & Gile, Contract #31 dated April, 1853
(DCSO records, Volume 8 Page 3132)

Set ¼ sec. post, from which
 A Fir 8" dia. bears N.4°W., 12 lks. dist.
 A Fir 12" dia. bears S.5°E., 16 lks. dist.

Volume 2 Page 265 - Date ? - By ?

Set Sandstone 5"x5"x18" for 1/4 corner on South side Sec. 32
Alder 20" dia. bears S.50°20'W., 75 lks. dist.
W.Oak 20" dia. bears N.65°45'E., 115 lks. dist.
Gov't BTs were gone. Old rock was found set by previous
Surveyor Co. Surveyor.

A. Boyer - Willis Ausland, January 1942 - C.S. File 36/18
Volume 4 Pg 86

24" Alder S.50°20'W., 49.5 ft. still standing but partly
decayed. Found 5x5x8 rock. New trees set:
 8" Fir N.72°W., 37.7 ft.
 8" Forked Ash S.57°E., 35.3 ft.

Milo E. Godfrey, Dep. Co. Surveyor - Vernon Tracy; Mike Stone
November 1962 - C.S. File 49/123-52

Found - Rock called for in earlier renewals.
 14" W.Fir snag N.72°W., 37.7 ft. standing but
 rotten. Scribing visible "¼ BT".
 No trace of Boyer's SE tree.
 Rotten Alder snag S.50½°W., 49.5 ft. no markings
 found.
 Clump of Ash growing out of old stump hole,
 N.65 ¾°E., 76.0 ft. (Renewal calls for 20"
 W.Oak N.65 ¾°E., 75.9 ft.)
 No trace of original BTs found.
Set brass cap alongside rock mkd:
 County Surveyors ¼ S32 T24S
 Office, 1962 S5 T25S R6W
New BTs - 11" W.OAK N.51°W., 45.7 ft. mkd. ¼ S32 CS BT.
 12" Ash S.50°W., 28.2 ft. mkd. ¼ S5 CS BT.
Cor. lies in fence cor. fences South & West from corner.

(Cont. next page)

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5; 32, T24-6

| | | | |
|-------|-------|-------------|-------|
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |

Mark Smalley - For: Roseburg Forest Products - April 1998 -
M 128-74

Found - 1962 County brass cap on iron pipe & sandstone.
16" W.Oak, N.51°W., 45.7', healed.
12" Ash, S.50°W., 28.2', not tree, Ash clump.
Scribed- 9" Ash, South 37.6', "¼ S BT"
22" Fir, S.28°E., 105.7', "¼ S BT"