

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33; & 4 & 5 of T26-6

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post cor. to secs. 32, 33, 4 and 5, from which
A Y.Oak 15" dia. bears S.4°W., 23 lks dist.
A W.Oak 28" dia. bears S.52°E., 178 lks. dist.
A W.Oak 12" dia. bears N.84°E., 81 lks. dist.
A W.Oak 16" dia. bears N.83°W., 171 lks. dist.

Milo E. Godfrey's Crew - Vernon Tracy; Mike Stone
February 1963 - C.S. File 49/123

Found - 32" W.Oak snag S.52°E., 117.5 ft. with scribe marks
B. Oak stump S.4°W., 15.2 ft. rotted, no scribing.
25" W.Oak N.83°W., 112.9 ft. showing good scar.
20" W.Oak N.84°E., 53.5 ft. shows faint scar.

Set - Brass cap at cor. mkd: County Surveyor's Office
1963 T25S R6W S32|S33
T26S R6W S 5|S 4

New BTs - 16" B.Oak bears S.49°E., 69.3 ft. mkd. T26S R6W
S4 CS BT.
13" W.Oak bears S.29°W., 29.3 ft. mkd. T26S R6W
S5 CS BT.
14" W.Oak bears N.39°W., 10.6 ft. mkd. T25S R6W
S32 CS BT.
15" W.Oak bears N.57°E., 26.5 ft. mkd. T25S R6W
S33 CS BT.

DCSO-GIS Corner visitation - 6/23/2004 - Typed: 1/26/2011 -
C.S. File 67/33-1

Monument - BC/IP 1.25"
Comment - ok