

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, contract #31 dated April, 1853  
(DCSO records, Volume 9 Page 3833)

-----  
Set post cor. to secs 28, 29, 32 and 33, from which  
A W.Oak 9" dia. bears S.11°E., 72 lks. dist.  
A W.Oak 36" dia. bears S.26½°W., 65 lks. dist.  
A Y.Oak 6" dia. bears N.70°W., 41 lks. dist.  
A Y.Oak 15" dia. bears N.53½°E., 72 lks. dist.

A. Boyer, April 18, 1936 - For: Joe Winniford & J.W. Cook  
C.S. File 23/27

-----  
Reset from stump of orig. BT in Sec. 32. 3/4" Bolt.  
Other BTs destroyed. Mark new BTs as follows:  
W.Oak 12" dia. N.75°E., 32 ft.  
W.Oak 8" dia. S.16°E., 11.4 ft.  
B.Oak 12" dia. S.44°W., 9.4 ft.  
Fir 13" dia. N.30°W., 34.4 ft.

Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy; Mike  
Stone - January, 1963 - C.S. File 49/123-68

-----  
Found - ¾" Iron bolt with square head.  
13" Fir snag N.30°W., 34.4 ft. scribing visible  
"S29" CS BT.  
15" B.Oak S.44°W., 9.4 ft. shows 2 very good axe  
scars, good condition.  
13" W.Oak S.16°E., 11.4 ft. shows 2 very good axe  
scars, good condition.  
18" W.Oak N.75°E., 32.0 ft. shows 2 good axe scars.  
Good condition.

Alongside bolt at cor. set Brass cap mkd. County Surveyors  
T25S R6W S29|S28 Office 1963  
S32|S33

New BT - 7" D.Fir N.11°W., 18.0 ft. mkd. T25S R6W S29 CS BT.

Fd. I.P. w/Brass cap. J. Artman, Oct. 1991 - M 113-74  
Found OK, April 1994 by Pieske - M118-80.

Fd. Ok by Douglas Co. Surveyors Office - Randall W. Smith,  
Deputy - Stephen J. Flause - 1/16/2002 - C.S. File 66/32-9

DCSO-GIS Corner visitation - 6/28/2044 - Typed: 1/24/2011 -  
C.S. File 67/33-1

-----  
Monument - 1.25" BC/IP  
Comment - OK Cont.

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch - June 23, 2014 - C.S. File 67/41-25

- 
- Found - A 3/4" dia., iron bolt with a 1" square top is plumb and protruding 2" above ground. 1936
- A 2 1/2" dia., brass cap (properly mkd) on a 1 1/4" I.D. iron pipe leaning slightly SE'ly protruding 10" above ground on the NW'ly edge of the 1936 monument. 1963
- No evidence remains of the Orig. BTs
- A W.Oak 12" dia., now a double trunk W.Oak with a larger tractor scar (covering the blaze scar?) on the 30" dia., most westerly trunk. The C.R.C. of the double trunk bears N.75°E., 34.6 ft. (rec. N.75°E., 32 ft.) 1936
- A W.Oak 8" dia., now a 15" dia., W.Oak with a fully healed double blaze (hardly visible) bears S.16°E., 11.4 ft. (as per rec) 1936
- A B.Oak 12" dia., now a 2 ft. tall B.Oak stump (partly in ground, partly kicked out of position) with clear evidence of healed face inside; bears S.44°W., 10.4 ft. (rec. S.44°W., 9.4 ft. more at a face measurement) 1936
- A fir 13" dia., now a shallow root depression; bears N.30°W., 34.4 ft. (as per record) 1936
- No evidence of the 1963 renewal BT remains.
- New - A 5/8" iron rod protruding approx 8" above ground and set just east'ly of a fence post bears S.56 3/4°W., 117.7 ft. (this bearing and dist. from the corner agrees with the map relationship shown in the DCSO records on Map M89-35)
- An 18" dia., W.Oak double blazed and scribed "T25S R6W S29 CS" "BT" bears N.4 1/2°W., 54.6 ft.
- Note - Monument is at easterly edge of large mown yard in a mixed oak and fir woods. A fence running approx. N.80°E., is approx. 50 ft south of corner.
- Compass decl. 15 1/2°E.