TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853 (DCSO records, Volume 9 Page 3835)

Set ¼ sec. post, from which
A W.oak 12" dia. bears N.3½°W., 378 lks. dist.
A W.Oak 13" dia. bears N.9°E., 392 lks. dist.

Milo E. Godfrey, Dep. Co. Surveyor - Vernon Tracy; M. Stone August, 1962 - C.S. File 49/123-22

Found - W.Oak now 32", N.9°E., 258.7 ft. Cut open & found good scribing "B".
W.Oak now 34", N.3½°W., 249.5 ft. No scar visible. Did not open.
Both old bearing trees in good condition.
Set brass cap at cor. mkd: County Surveyor's Office, 1962
T25S R6W ¼ S20|S21
New BTs - 17" W.Oak N.30°W., 39.8 ft. mkd: ¼ S20 CS BT.
36" D.Fir N.25°E., 69.8 ft. mkd: ¼ S21 CS BT.
Fence corner bears West, 4 ft. (fences North & East.)

Douglas County Surveyors Office - Randall Smith & Stephen Flause - 7/5/95 - C.S. 64/63-13

Mon. Fd.- 2½" Dia. DCSO Brass cap on a 1½" o.d. Iron pipe protrudes 12" above ground.
Accessories Fd. -
12" now 37" dia. W.Oak, no blaze visible, bears N.3½°W., 248'.
13" now 33" dia. W.Oak, with a previously opened blaze no scribing visible. bears N.9°E., 261'.
17" now 25" dia. W.Oak, with a fully healed double blaze, bears N.30°W., 39.8'.
36" now double trunked 4' high D.Fir stump with a fully healed double blaze on 36" dia. south trunk, center of south trunk bears N.25°E. 69.8'.
New Accessories -
14" dia. W.Oak, double blazed and scribed "¼ S21 CS BT", bears S.43°E., 84.3'.
corner lies near the intersection of a north and east running fence line 3' east of north fence a 1' north of east fence.

Fd. Ok by Carl Sweeden, - Aug. 1998 - M130-22.