

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Sec Cor for 4, 5, 8 & 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853  
(DCSO records, Volume 9 Page 3838)

-----  
Set post cor. to secs. 4, 5, 8 & 9 from which  
A Y.Oak 11" dia. bears N.28½°W., 21 lks. dist.  
A Y.Oak 12" dia. bears N.27½°E., 40 lks. dist.  
A Y.Oak 10" dia. bears S.32°E., 49 lks. dist.  
A Y.Oak 15" dia. bears S.31¼°W., 76 lks. dist.

M.B. Germond, Dep. Co. Surveyor - For: Cal Durling  
March 17, 1909 - Volume 2 Page 157

-----  
Set stone of sand 6" x 10" x 20" and note old BTs standing.

James W. Byron, Milo Godfrey, S.A. Bilow - November 12, 1958  
C.S. File 49/123-1

-----  
Found - Orig. 15" now 24" W.Oak S.31¼°W., 50.3 ft. shows  
old scar, center rotted.  
Orig. 12" now 24" Oak stump N.27½°E., 26.4 ft.  
shows good reverse scribing inside stump "BT".  
Remains of old Oak stump that checks bearing &  
distance for original SE and NW BTs.

Set brass cap at cor. mkd:  $\frac{S\ 5}{S\ 8} | \frac{S\ 4}{S\ 9}$  T25S R6W County Surveyor's  
Office, 1958

(Sketch in C.S. file showing relationship to fences.)  
New BTs - 7" R.Fir bears N.10°E., 55.4 ft. scribed S4 T25S  
R6W CS BT.  
14 W.Oak bears S.46°E., 58.3 ft. scribed S 9 T25S  
R6W CS BT.  
10" W.Oak bears N.49°W., 17.9 ft. scribed S 5 T25S  
R6W CS BT.  
24" W.Oak bears S.32°W., 52.0 ft. scribed S 9 T25S  
R6W CS BT.

Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy; M.Stone  
November 1962 - C.S. File 49/123-49

-----  
Found - Brass cap set in 1958.  
14" W.Oak S.46°E., 58.3 ft scribing vis., tree alive  
Found - 24" W.Oak S.32°W., 52.0 ft. scribing visible, tree  
standing but dead.  
10" W.Oak N.49°W., 17.9 ft. scribing visible, tree  
standing but dead.  
7" Fir N.10°E., 55.4 ft scribing visible, dead & down  
New BTs - 8" W.Oak S.25½°W., 74.5 ft mkd: T25S R6W S8 CS BT  
continued next page

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Sec Cor for 4, 5, 8 & 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

6" D.Fir N.80°W., 71.9 ft. mkd: S5 CS BT. 7" Madrone N.23°E. 73.5 ft mkd: T25S R6W S4 CS BT
Fd. ok by D.Edwards - 11/1997 - 1998-0001 A&B
Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 2/3/98 - C.S. File 64/79-14 ----- Found - 2½" dia., brass cap on a 1½" O.D. iron pipe, protrudes 6" above ground. 1958 10" W.Oak, now root hole, bears N.49°W., 17.9 ft. (Agrees with rec.) 1958 24" W.Oak, now rotted remains, no scribing visible, root hole, bears S.32°W., 52.0 ft. (Agrees with rec.) 1958 8" now 11" dia., W.Oak with a fully healed double blaze, bears S.22½°W., 74.5 ft. (Rec. S.25½°W., 74.5 ft.) 1962 No other BT's found. New BTs- 11" dia., B.Oak, double blazed and scribed "T25S R6W S5 CS BT", bears N.49°W., 35.4 ft. 6" dia., gnarly B.Oak, double blazed and scribed "X BT", bears N.4½°E., 63.6 ft. 20" dia., W.Oak, that forms a fence corner with wire ingrown is single blaze 4 ft. above ground "X CS BT", bears S.88½°E., 71.5 ft.
Found OK by D. Edwards, Jan. 2000 - CS65/29-2
DCSO-GIS Corner visitation - 6/30/2004 - Typed: 1/24/2011 - C.S. File 67/33-1 ----- Monument - 1.25" BC/IP Comment - OK
Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch - Sept. 9, 2013 - C.S. File 67/40-2 ----- Condition report Found - (Monument) As recorded. As recorded in 1998 except the new in 1962 SW Oak BT Now a 14" dia., 1½ ft. tall cut oak stump showing evidence of lower blaze; bears S.22½°W., 74.5 ft. (as per rec.) 1998 BT tag is re-nailed to blazed face of stump. Monument is at corner of fences running N-S and West. Monument is on West edge of N-S running ranch access road.