

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853
(DCSO records, Volume 9 Page 3830)

Set post cor. to secs. 15, 16, 21 and 22, from which
A Y.Oak 18" dia. bears S.47½°E., 224 lks. dist.
A Y.Oak 14" dia. bears S.22°W., 115 lks. dist.
A Y.Oak 24" dia. bears N.46¼°W., 462 lks. dist.
A Y.Oak 15" dia. bears N.78½°E., 304 lks. dist.

Milo E. Godfrey, Dep. Co. Surveyor - Vernon Tracy; Mike
Stone - July 20, 1962 -C.S. File 49/123-13

Found - B.Oak now 36" N.78½°E., 200.6 ft. previously
opened but not deep enough. Chopped open
& found good reverse scribing "BT". Tree
hollow and dying.
Oak, uprooted & down, N.44°W., (instead of N.46¼°W)
304.9 ft., badly rotted but fragments of re-
verse scribing found.
Stump hole S.22°W., 74.9 ft., stump hole S.47½°E.,
147.8 ft.
Set brass cap at cor. mkd: County Surveyor's T25S R6W S16 S15
Office, 1962 S21 S22
New BTs - 14" W.Oak S.21°W., 60.6 ft. mkd: T25S R6W S21 CS BT.
18" D.Fir N.55°W., 49.5 ft. mkd: T25S R6W S16 CS BT.
8" W.Oak S.48°E., 63.4 ft. mkd: T25S R6W S22 CS BT.
21" W.Oak N.78½°E., 160.1 ft. mkd: T25S R6W S15 CSBT
A scribed Oak stake in fence corner (fences W. & N.) bears
N.5°W., 6.2 ft.

Douglas County Surveyors Office - Randall Smith & Stephen
Flause - 7/5/95 - C.S. 64/63-14

Mon. Fd.- 2½" Dia. DCSO Brass cap on 1½" O.D. Iron pipe
protrudes 7" above ground.
Accessories Fd.-
15" now 36" Dia. down B.Oak, with a previously
opened blaze scribing found "BT" remaining 1'
high stump, bears N.78°E., 200.6'.
No evidence of any other orig. BT's found
14" now 18" Dia. W.Oak, with a fully healed double
blaze, bears S.18 3/4°W., 60.6'

(Cont. Next Page)

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New -	18" now 36" Dia. 1' high D.Fir stump, with a fully healed lower blaze visible, bears N.56½°W., 49.5'. 8" now 13" Dia. W.Oak, with a fully healed double blaze bears S.49 3/4°E., 63.4'. 21" now 27" Dia. W.Oak, with a fully healed double blaze, bears N.76½°E., 160.1'. 11" Dia. W.Oak, double blaze and scribed "T25S R6W S16 CS BT", bears N.49 3/4°W., 115'.
Fd. 1962 DCS0 BCIP Per C.S. 64/63-14 - 6/2018 by A. DeGroot NAD 83 (2011) Lat: 43°23'19.34855"N Long: 123°24'22.49020"W	