

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853
(DCSO records, Volume 9 Page 3831)

Set post cor. to secs. 9, 10, 15 and 16, from which
A Y.Oak 12" dia. bears S.15°E., 30 lks. dist.
A Y.Oak 16" dia. bears S.41°W., 50 lks. dist.
A Y.Oak 12" dia. bears N.64°W., 37 lks. dist.
A W.Oak 12" dia. bears N.33°E., 45 lks. dist.

James W. Byron, For: A. Stephens - Feb. 20, 1956 - C.S. File
47/50 & M2-6

Found - Orig. NE BT, N.33°E., 29.7 ft. now 24" W.Oak. I
open near base & find scribed "BT".
Also find stump hole for orig. NW BT. Checks for
bearing & distance.
Also found 6"x6"x6" stone chiseled + on top at cor.
Set brass cap mkd. Sec. Cor. S9|S10 T25S R6W County Surveyor
S16|S15 Office, 1956.
Set chiseled stone alongside brass cap. Sketch in CS File.
Blazed & Scribed:
6" W.Oak S.45°E., 17.3 ft. S15 CS BT.
10" W.Oak N.46°W., 67.0 ft. S9 CS BT.
8" W.Oak S.38°W., 7.5 ft. S16 CS BT.
Reblazed & scribed orig. NE BT, S10 CS BT.

Fd. Brass Cap & BTs - Raymond Brown, L.S. #2391 - For: Roaland
Clark - Jan. 1994 - M 119-14

Douglas Co. Surveyors Office - Randall Smith & Stephen Flauser
- Oct. 30, 1997 - C.S. 64/78-22

CONDITION REPORT ONLY

Mon. Fd.- 2½" Brass cap on a 1½" O.D. iron pipe protrudes
10" above ground. 1956.
Stone along west edge of BC/IP shows a chiseled +
on top flush with ground. source unknown.
Bt's Fd.- 12" now 27" dia. W.Oak, with a previously opened
partially healed blaze, no scribing visible,
bears N.30°E., 29.7' (rec. N.33°E., 29.7',
agrees with a 1962 BT tag) OBT.
6" now 9" dia. W.Oak, with a fully healed double
blaze, bears S.47°E., 17.3' (rec. S.45°E.,
17.3')

(Cont. next page)

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 and 16

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

<p>10" now 11" dia. W.Oak, with a fully healed double blaze, bears N.46°W., 67' (agrees with rec. S.38°W., 7.5' dist. fits blaze) 1956. Fence corner running east & south bears N.65°E., 3'</p>
<p>DCSO-GIS Corner visitation - 7/1/2004 - Typed: 1/25/2011 - C.S. File 67/33-1</p> <p>-----</p> <p>Monument - Orig. post/stone (1.25") Comment - ok</p>
<p>FD. Ok by D. Edwards 10/2006 - 2006-0092 A&B Fd. 1956 DCSO BCIP Per C.S. 64/78-22 - 6/2018 by A. DeGroot</p>