

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder & Gile, Contract #31 dated April, 1853
(DCSO records, Volume 9 Page 3832)

Set ¼ sec. post, (on top of ridge, course NE and SW.)
from which

A W.Oak 36" dia. bears S.54°W., 92 lks. dist.

A W.Oak 16" dia. bears S.85°E., 45 lks. dist.

Milo E. Godfrey, Deputy - Mike Stone - October 15, 1962
C.S. File 49/123-37

Found - 36" W.Oak, nearly dead, S.54°W., 58.3 ft. (record
60.7 ft.) Chopped open & found good scribing
"BT".

24" W.Oak S.85°E., 28.5 ft. (Rec. 29.7 ft.) chopped
open & found good scribing on old face, part
of "4" & "S".

Set brass cap at cor. mkd: County Surveyors T25S R6W ¼ S9|S10
Office, 1962

New BTs - 9" W.Oak S.88°W., 16.6 ft. mkd: ¼ S9 CS BT.

10" W.Oak S.41°E., 32.3 ft. mkd: ¼ S10 CS BT.

Corner lies directly on top of ridge.

Fd. Brass Cap & BTs, R Brown, 1/1994 - M 119-14
Fd 1962 BC, 11/2015 - C.Sweeden M170-18