

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder & Gile, Contract #31 dated April, 1853
(DCSO records, Volume 9 Page 3832)

Set post cor. to secs. 3, 4, 9 and 10, from which
A Fir 15" dia. bears S.2°E., 35 lks. dist.
A Laurel, 8" dia. bears N.63°E., 16 lks. dist.
A Y.Oak 12" dia. bears N.37°W., 25 lks. dist.
A Laurel, 7" dia. bears S.68°W., 55 lks. dist.

G.G. Stewart, For: J.A. & Fay Leatherwood, March 22, 1922
C.S. File 2/14 and Volume 3 Page 112

Reset from one O.B.T. Others gone.
Set rock for corner. Marked:
A 48" Fir S.58°W., 25.0 ft.
8" Fir N.68°E., 14 ft.
24" Fir N.19°W., 24.6 ft.
15" Fir S.2°E., 35.0 ft. (O.B.T.) (per M.E.G. should be
35 lks.)

Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy; Mike
Stone - November 1962 - C.S. File 49/123-44

Found - 2 rocks, buried, largest 6"x10"x16". (no marks)
Rotted Fir stump N.19°W., 24.6 ft. scribing
visible on old face, "S" & "BT".
40" Fir snag S.58°W., 25.0 ft. shows good axe scar.
16" Fir N.68°E., 14.0 ft. shows good scar.
Orig. SE BT is uprooted & out of position,
impossible to tell where it stood. Scribing
visible.
Set brass cap at cor. mkd. County Surveyor's T25S R6W S4|S3
(Set rocks alongside) Office, 1962 S9|S10
New BTs - Rescribe 16" D.Fir N.68°E., 14.0 ft. (to face) mkd.
S 3 CS BT.
11" I.Cedar S.32°E., 69.0 ft mkd. T25S R6W S10 CSBT
21" D.Fir S.10°W., 51.3 ft. mkd. T25S R6W S 9 CS BT
13" I.Cedar S.75°W., 94.2 ft. mkd. T25S R6W S9 CSBT
No trees near to NW fence cor. bears N.52°W., 33.0 ft.

Found & Used, BLM Dependent Resurvey, 1972 - (DCSO records
Volume 36 Page 15003-04)

Fd BC & BTs - R. Brown - For: Roland Clark - 1/94 - M 119-14