

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 34 & 3 of T 26-6

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Original - Elder & Gile, Contract #31 dated April, 1853

Set 1/4 sec. post, from which

A Laurel, 14" dia. bears N.47°E., 34 lks. dist.

A Laurel, 14" dia. bears S.54°E., 54 lks. dist.

A.R. Evans - Bob Matthews; E.A. Jennie, Witnesses
Nov. 1949 - C.S. File 43/167 - M 16-25

Found 36" Fir line tree called for in notes, measured
called distances, location fits Laurel tree for direction
and distance. Laurel blazed but rotted out.

Set - 3/4" Iron rod, from which

12" Fir bears S.88°E., 17.9 ft. mkd. 1/4 S 3 CSBT.

No suitable tree available in Sec. 34.

Searched for, Not found Fd. old laurel which had been chopped
open on east side scribe MK (not orig.), June, 1963 - M.E.G.
- C.S. File 49/123-84

Mark F. Smalley, L.S. # 2354 - For: Roseburg Resources Co. -
Feb. & Mar. 1993 - M 117-7.

Found - 3/4" Bolt with nut, bent over.

No evidence of BT. scribed by Evens.

Set - 5/8"x48" I.R. & alum. cap.

BT's - 8" Fir, S.61°W., 16.5', "1/4 BT"

7" Fir, S.4°E., 16.2', "1/4 BT"

9" Fir, N.64°E., 3.7', "1/4 BT"

8" Fir, N.37°W., 27.3', "1/4 BT"

Fd Ok by K. DeGroot - May 1994 - M 119-30

Fd. OK by K. DeGroot, May 1999 - M132-1