TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 & 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853 (DCSO records, Volume 9 Page 3831

Set ¼ sec post, from which
A Y.oak 18" dia. bears S.73°W., 41 lks. dist.
A Y.Oak 15" dia. bears N.12°W., 45 lks. dist.

Milo E. Godfrey, Dep. Co. Surveyor - Vernon Tracy; M. Stone August, 1962 - C.S. File 49/123-24

Found - B.Oak now 24", N.22°W., (instead of N.12°W.) 29.7 ft.. Chopped open & found reverse scribing "¼". Center of tree rotted away - hollow.
B.Oak now 28", S.69°W., (instead of S.73°W.) 27.1'. Chop open & find good scribing "T", tree in good condition.
Set brass cap at cor. mkd: County Surveyor's T25S R6W ¼ S10/S15 Office, 1962
New BTs - 15" D.Fir S.77°W., 15.3 ft. mkd. ¼ S15 CS BT.
6" D.Fir N.23°E., 10.6 ft. mkd: ¼ S10 CS BT.
Note - Set corner at intersection of distances, since neither distance fit at intersection of bearings.

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 2/5/98 - C.S. File 64/79-22

Found - 2½" dia., brass cap on a 1½" O.D. iron pipe, protrudes 12" above ground. 1962
18" now 24" dia., 20 ft. high B.Oak snag previously opened and rotted, no scribing visible bears S.69°W., 27.1 ft. (Agrees with 1962 rec.) OBT
15" now 22" dia., 1 ft. high Oak stump, previously opened and rotted, no scribing visible, bears N.22°W., 29.7 ft. (Agrees with 1962 rec.)OBT
15" now 25" dia., D.Fir with a fully healed double blaze, bears S.77°W., 15.3 ft. (Agrees with rec.) 1962
6" now 14" dia., D.Fir with a fully healed double blaze, bears N.23°E., 10.6 ft. (Agrees with rec.)1962
New BTs - 9" dia. D.Fir, double blazed and scribed "¼ S15 CS BT", bears S.12½°W., 12.8 ft.
18" dia. Madrone double blazed and scribed "¼ S15 CS BT", bears S.38½°E., 25.5 ft.