

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Original - Elder &amp; Gile, Contract #31 dated April, 1853 (DCSO records, Volume 9 Page 3832)</p> <p>-----</p> <p>Set ¼ Sec. post, from which     A Laurel, 15" dia. bears S.15½°E., 58 lks. dist.     A Y.oak 12" dia. bears N.67°W., 100 lks. dist.</p>
<p>G.G. Stewart, For: J.A. &amp; Fay Leatherwood, March 22, 1922 C.S. File 2/14 and Volume 3 Page 112</p> <p>-----</p> <p>Re-established midway between 2-3-10-11 and 3-4-9-10. Set 4" square Oak Post. Marked:     24" Fir S.33°E., 24.8 ft.     18" Fir N.42°W., 11 ft.</p>
<p>Searched for, not found - Jan. 1963, C.S. File 49/123-58</p>
<p>BLM Dependent Resurvey, June 5-21, 1972 - Albright and Bowder (DCSO records, Volume 36 Page 15002)</p> <p>-----</p> <p>Point for the ¼ sec. cor. secs. 3 &amp; 10, at proportionate distance, there is no remaining evidence of the original cor. Set an iron post, 28" long 2½" dia. 20" in the ground, with brass cap marked:    T 25 S R 6 W                             ¼        S 3   S 10   1972</p> <p>from which     A Fir 12" dia. bears N.54½°W., 126½ lks. mkd. ¼ S 3 BT.     An Oak 7" dia. bears S.67½°W., 99 lks. mkd. ¼ S 10 BT. The corner is located .45 chs. North of wire fence, extending generally E. and W.</p>
<p>Found OK June 1994 by K. DeGroot - M119-34. Fd. Ok Nov. 2013 by C. Sweeden M165-78</p>
<p> </p>