

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

G.G. Stewart, Deputy - For: J.A. & Fay Leatherwood
March 22, 1922 - Volume 3 Page 112

Set a rock for center Section 3 and marked:
A 14" Fir S54°W., 37.7 ft.
A 24" Fir S.22°E., 62.8 ft.

Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy and
Mike Stone - November 1962 - C.S. File 49/123-40

Found - Rock (top 5" x 10") set by Stewart. "X" chiseled
in top of rock.
Fir snag 24" dia. S.54°W., 37.7 ft. Cut open and
found good scribing.
Rotten & badly burned Fir snag S.22°E., 62.8 ft. No
marks.
Alongside rock at cor., Set Iron pipe with brass cap marked:
"County Surveyor's Office, 1962 T25S R6W Cent. ¼ S 3 +"
New BTs - 15" D.Fir S.12°W., 13.7 ft. mkd. "C ¼ S3 CS BT".
20" I. Cedar S.48°E., 59.8 ft. mkd. "C ¼ S3 CS BT."

Kristian DeGroot - surveyed for Roseburg Forest Products,
June 1994 - M119-34.

Set - 5/8" x 30" iron rod 26" in the ground with a 2" alum.
cap stamped:
T25S R6W
C ¼ + S3
1994
PLS 1941
New Accessories -
12" D.Fir, bears N.28°30'E., 9.4 ft. scribed "C¼ S3 BT"
12" D.Fir, bears N.26°30'W., 12.5 ft. scribed "C¼ S3BT"
1" iron pipe with a 2½" brass cap stamped "COUNTY
SURVEYORS OFFICE CENT 1/4 S3 1962' firmly set
projecting 6" above the ground, bears N.52°51'34"E.
18.17 ft. (set by Stewart in 1922, renewed in 1962)
5/8" x 30" iron rod set 24" in the ground in a 24" dia.
mound of stone with a 1½" alum cap stamped "PROP
COR. PLS 1941" bears N.0°02'12"W., 220.41 ft.

Found OK Feb. 1997 by D. Edwards - M 126-53
Fd. Ok by M. Heimburger, 2/2013 - M164-60