

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Sec Cor for 26, 27, 34 & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder & Gile, Contract #31 dated April, 1853  
(DCSO records, Volume 9, Page 3822)

-----  
Set post cor. to secs. 26, 27, 34 and 35, from which  
A Y.Oak 12" dia. bears N.55°E., 223 lks. dist.  
A Y.Oak 15" dia. bears N.51°W., 175 lks. dist.  
A Y.Oak 10" dia. bears S.40½°E., 222 lks. dist.  
A W.Oak 40" dia. bears S.87½°W., 116 lks. dist.

N.E. Richardson; M.E. Godfrey; Les Kershner - Dec. 11, 1946  
C.S. File 39/38 - M 13-12

-----  
Set corner from one O.B.T., a 15" Oak N.51°W., 175 lks. Tree  
is down but found B.T. mark.  
Set an axle 1½" x 54", 6" disk at top and a 3"x3"x36" Oak  
stake from which,  
A 16" Fir S.37½°W., 40.3 ft.  
A 14" Fir N.65¾°W., 85.1 ft.  
No tree NE.  
A 20" Fir S.39¼°E., 49.1 ft.

Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy; Mike  
Stone - April 11, 1963 - C.S. File 49/123-76

-----  
Found - Axle as called for by Richardson.  
20" Fir N.65¾°W., 85.1 ft. shows very plain scars.  
Did not open.  
The SE and SW BTs mkd. in 1946 have both been cut.  
Found stumps of both, which show very good axe  
scars, did not open.  
DID NOT SET BRASS CAP.  
New BTs - 4" D.Fir S.50°W., 14.2 ft. mkd. S34 CS BT.  
12" D.Fir N.62½°E., 114.0 ft. mkd. T25S R6W S26 CSBT  
6" D.Fir S.85°E., 55.4 ft. mkd. S35 CS BT.  
Cor. lies in fence corner, fences E. & S. from corner.

Fd 1½" Axle & 3 BTs by K. DeGroot, May 1994 - M 119-30  
Fd. OK - Kristian DeGroot - Nov. 1995 - M 123-15

Found OK by DeGroot, Dec. 1997 - 1998-0011  
Fd. OK by K.Degroot, May 1999 - M132-1