

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853
(DCSO records, Volume 9 Page 3823)

Set ¼ sec. post, from which
 A Y.Oak 20" dia. bears S.3½°W., 1024 lks. dist.
 A Maple, 12" dia. bears S.72¼°E., 515 lks. dist.

Milo E. Godfrey, Dep. Co. Surveyor - Vernon Tracy; Mike
Stone - Dec. 1962-Jan. 1963 - C.S. File 49/123-63

Found - 30" W.Oak N.60°W., 61.4 ft., down & dead, cut open
 & found scribing.

 No trace of SE tree.

Cor. position falls in center of small creek.

Set WITNESS CORNER 25 ft. West of ¼ corner - Set brass cap mkd
County Surveyor's Office 1963 T25S R6W WC ¼ S23 25 ft. E.
to Cor. S26

New BTs - 13" W.Oak S.37°W., 10.2 ft. mkd: WC ¼ S26 CS BT.
 18" W.Oak N.77°E., 71.2 ft. mkd: WC ¼ S23 CS BT.

DCSO-GIS Corner visitation - 7/8/2004 - Typed: 1/25/2011 -
C.S. File 67/33-1

Monument - BC/IP 1.5"
Comment - (Needs) rehab