

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder & Gile, Contract #31 dated April, 1853
(DCSO records, Volume 9 Page 3818)

Set 1/4 sec. post, from which
 A Y.Oak 30" dia. bears N.56°W., 130 lks. dist.
 A Y.Oak 11" dia. bears N.33°E., 131 lks. dist.

Milo E. Godfrey, Dep. Co. Surveyor - Vernon Tracy; Mike Stone
Dec. 1962 - C.S. File 49/123-61

Found - 38" dead Oak snag N.56°W., 85.8 ft. Cut open & found
 good reverse scribing "1/4S" & "BT."
 Rotted remains of Oak stump N.33°E., 86.5 ft. No
 marks left.

Set brass cap at cor. mkd: County Surveyors Office, 1962
 T25S R6W 1/4 S23|S24

New BTs - 9" B.Oak S.46°E., 20.2 ft. mkd: 1/4 S24 CS BT.
 18" double Madrone N.65°W., 22.6 ft. mkd: 1/4 S23
 CS BT.

A north & south fence line bears West 137 ft.

Found OK by B. Shaner, July 1997 - M 124-59 & C.S. 65/15-10 D