TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias Description
Alias Description
Alias Description
Alias Description

Original - Elder & Gile, Contract #31 dated April, 1853 (DCSO records, Volume 9, Page 3821)

Set ¼ sec. post, from which
A Y.Oak 18" dia. bears S.86°W., 133 lks. dist.
A Y.Oak 8" dia. bears N.28°E., 30 lks. dist.

C.W. Springer, Deputy Co. Surveyor - Wit. Bergh; Davison; and Bemis - For: Davison & Bemis - Feb. 1923 - Volume 3 Page 138, Field Book 60.

Reset from 1 original BT and evidence of second BT. Renewed cor. with an iron pipe 1½" x 30" driven in ground, from which
A B.Oak 16" dia. bears S.59°W., 58 lks.
A B.Oak bears N.28°E., 30 lks.

Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy, Mike Stone - November, 1962 - C.S. File 49/123-54

Found - 1¼" Iron pipe set by Springer, 1923.
B.Oak, now 20", N.28°E., 19.8 ft. Cut open & found scribing, part of "BT" on badly rotted old face.
16" B.Oak S.59°W., 38.3 ft Tree down & badly burned no scribing fd, some old axe marks visible.
No trace of original SW BT.
Set brass cap at cor. mkd: County Surveyor's Office 1962
T25S R6W ¼ S2|S1
New BTs - 8" W.Oak N.81°W., 16.0 ft. mkd: ¼ S 2 CS BT.
16" B.Oak N.47°E., 56.3 ft. mkd: ¼ S 1 CS BT.
Corner lies on top of ridge in fence corner, old fences running North, South and West.

Found OK by K. Hoffine, March 2000 - M134-64

DCSO-GIS Corner visitation - 7/7/2004 - Typed: 01/25/2011 - C.S. File 67/33-1

Monument - BC/IP 1.25"
Comment - ok

FD BC per rec. 4/2023 by B Heichel - 2023-0014