TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853 (DCSO records, Volume 9 Page 3820)

Set ¼ sec. post, from which
A Y.Oak, 16" dia. bears N.71¾°E., 796 lks. dist.
A W.Oak 24" dia. bears N.52°W., 857 lks. dist.
No tree near S. of line.
N.56½°W., to a house.

Milo E. Godfrey, Dep. Co. Surveyor - Vernon Tracy; Mike Stone - Jan. 1963 - C.S. File 49/123-62

Found - 42" W.Oak dead, N.52°W., 565.6 ft. Cut open & found good scribing.
45" W.Oak, not B.Oak, N.71¾°E., 525.4 ft. No scar visible.
Set brass cap at cor. mkd: County Surveyors T25S R6W ¼ S12/S13 Office, 1963
New BT - 24" D.Fir S.5°E., 70.9 ft. mkd: ¼ S13 CS BT.
Reblaze- 45" W.Oak N.71¾°E., 525.4 ft. (to old face) mkd: ¼ S 12 CS BT.
Cor. lies inside right of way of Co. Rd. No. 10-A. Fence along North R/W line is 3 ft. North of corner.

Douglas Co. Surveyors Office - Randall Smith & Stephen Flause - Dec. 9, 1997 - C.S. 64/78-36

Mon. Fd.- 2½" brass cap on a 1½" o.d. iron pipe, protrudes 6" above ground. 1963
Accessories Fd.-
24" now 41" dia. D.Fir, with a fully healed single blaze, bears S.5°E., 70.9' (agrees with rec.) 1963.
24" now 47" dia. W.Oak, with a fully healed double blaze, bears N.71°E., 526.4' (rec. N.71°E., 525.4', dist. is a face measurement) OBT.
New Accessories -
Triple trunk Maple, double blazed and scribed "¼ S13 CS BT", on a 10" dia. middle trunk, root crown bears S.42°E., 64.3'.
15" dia. D.Fir double blazed and scribed "¼ S13 CS BT", bears S.35°W., 126.1'.
Corner lies on north side of county road 3' south of R/W fence. No trees available.