

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Sec Cor 13 & 24; 18 & 19 of T25-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post cor. to Secs. 13, 18, 19, and 24, from which
An Ash 10" dia. bears N.83½°W., 326 lks.
An Ash 8" dia. bears S.47°W., 297 lks.
Made trench, no other trees near.

Francis L. Ingram, Douglas Co. Surveyor - John Powell & Crew
May 1972 - C.S. File 56/16 and M42-61

This corner set from survey of Range line.

Set brass cap at cor. mkd. County Surveyor's R T 25 S R
Office 6 S 13 | S 18 5
1972 W S 24 | S 19 W

New BTs - 18" W.Oak N.75°W., 48.4 ft.scribed T25S R6W S13 CSBT
Bearing Objects:

5/8" Iron Rod North 10.0 ft.
5/8" Iron Rod South 10.0 ft.
5/8" Iron Rod East 10.0 ft.

Also set a steel fence post with survey mark sign alongside
Brass Cap.

Found Brass Cap, Bearing Tree & Objects - Glenn Baughman -
April 1993 - Vol. 18 Pg 1 A & B.

Fd. BC & 1 BT by D. Bentz, Sept. 1993 (Filed 12/94) 1994-108
Fd. OK, Oct. 1995 by Bentz - M123-20
Fd. OK, Oct. 1997 by Bentz - 1997-0133

Found Ok by Douglas Co. Surveyors Office - Randall W. Smith
& Stephen J. Flause - 10/9/1997 - C.S. File 64/79-9
Fd. Ok by Bentz - 11/1998 - M 130-71

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 3/29/1999 - C.S. File 66/8-30 & M131-50

Found: 2½" brass cap on a 1½" o.d. iron pipe, protrudes
6" above ground. 1972
18" now 25" w. oak with a fully healed double
blaze, bears N.52½°W., 67.8 ft.

East 5/8" B0 from 1972, bears N.6°E., 28.6 ft.

New: 1972 brass cap is sawn off & a yellow DCSO
plastic cap set in iron pipe center,
protrudes 3" above ground.
continued next page

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Sec Cor 13 & 24; 18 & 19 of T25-5

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Set - 2 3/8" brass cap on a 1 3/8" o.d. by 32" long iron pipe is set at new proportioned position, protrudes 7" above ground.
5" dia. D.Fir double blazed and scribed "X BT" bears N.36½°W., 80.5 ft.
1½" o.d. iron pipe, 1972, bears N.13 3/4°W. 29.59 ft.
Added 3/18/2021 -
This position was re-proportioned - See M131-50
Also found (1999) the 3 IRs that were set in 1972 and were 10 ft N, S & E. Of the previous corner location - See sketch in file.

March 15, 2000 - DCSO

Note - i.e. engineering will reference out this location - the existing monument will be buried.