

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 038020

PRIMARY CORNER DESCRIPTION NW Cor. Churchill DLC #38

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Dennis Hathorn, Contract #63 dated March 22, 1856

Set post deposited stone 7 x 4. Raised mound with trench as per instructions.

B.B. Irving, For: Rollo Wilson - Jan. 15, 1945 - C.S. File 38/5 - Vol. 4 Page 104

Drove Auto axle in old skein. Set 21.0 ft. from fence corner in County road. 3" underground.

Doug. County Surveyors Office - Vernon Tracy; Jack Heritage; V. Perron & Jim Rabe of BLM - Feb. 17, 1969 - C.S. 54/10-14

Found - 1 $\frac{3}{4}$ " Axle shaft 21.0 ft. West of fence corner 5" below surface of Co. Rd. at a point 20 ft. East of true corner, set 1" I.P.
Set Brass cap for Witness Corner mkd: County Surveyors T25S Office 1969 R7W Wit.
Cor. |NW DLC 39 20 ft.
W. to Cor.

No trees available for BTs.
At a point 26.0 ft. west of true corner & 46.0 ft. West of Wit. Cor., set a 5/8" x 30" I.R. in R/W fence on West side of road. Wit. Cor. lies 1.0 ft. No. & 1.0 ft. West of fence cor. fences N-S & E and on N. side of gateway on East side of road.

Fd. Ok by K. DeGroot 8/2000 2000-0083
Fd. OK by W. Rogers, 4/2002 - M137-39
FD. Ok by Ed Farr 11/2004 - 2004-0078