

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 049030

PRIMARY CORNER DESCRIPTION Int. L. Cor. DLC #49

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Dennis Hathorn, Contract #63 dated Mar. 22, 1856

Set post as per instructions, from which
An Ash 12" dia. bears North 13 lks. dist.

A. Boyer, D.C.S. - Wit. B.A. Lane; Will Long; John Paulson;
Ed Thompson, Husband of Mrs. Anna Emery Thompson - Oct. 26,
1937 - C.S. File 30/39

Set from stumps of two original Ash trees, the one North 13
lks. for BT, shows cut and old wood inside shell, decayed.
Set 4" Oak roller, ½" Iron bar in center, from which
W. Oak 24" bears S.87½°E., 56.8 ft.
W. Oak 12" bears S.44°W., 39.5 ft.
Both BTs marked Cl. 49 C.S.B.T.

Milo Godfrey; V. Tracy; C. Putnam - Oct. 19, 1961 - C.S.
File 49/76-14

Found - Rotted portions of Oak roller with ½" I.R. in each
end as set by Boyer.
Rock 9" x 11" x 12" above ground, set alongside.
W. Oak now 30", S.87½°E., 56.8 ft., shows good axe
scar. Tree in good condition.
W. Oak now 22", S.44°W., 39.5 ft. scar has been
opened previously, good scribing "Cl 9" visible
in opening, old face rotting. Reblaze &
scribe this tree.
At point where lower end of roller set in ground; Set Iron
Pipe with Brass cap mkd: County Surveyors Office 1961 T25S R7W
Int. L. D.L.C. 49

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 8/1/2000 - C.S. File 66/16-30

Found - 1961 DCS0 brass cap, iron pipe protrudes 6" above
ground and rock with no marks along south edge.
24" now 41" dia., W.Oak with a fully healed blaze,
bears S.87½°E., 56.8 ft. (1937)
12" now 27" dia., W.Oak with a fully healed single
blaze, bears S.44°W., 39.5 ft. (1937)
New - 12" dia., W.Oak double blazed & scribed "INT L DLC
49 CS BT" bears S.86°W., 21.5 ft.
7" dia., W.Oak double blazed & scribed "INT L DLC
49 CS BT" bears N.33°E., 106.0 ft.