

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION Tsp. Cor. SW Cor. Section 31

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, under Contract #57 dated April 12 1855 (DCSO records, Volume 9 Page 3858)

Set post corner of Tps. 25 and 26 S., Rs. 7 & 8 West, from which

- A Hemlock 10" dia., bears N.30°W., 30 lks.
- A Hemlock 18" dia., bears S.12°W., 8 lks.
- A Hemlock 24" dia., bears S.80°E., 24 lks.
- A Fir 20" dia., bears N.15°E., 36 lks.

Post found in good condition and all witness trees. GLO survey by S.C. & A.R. Flint, under Contract #392, 1881 (DCSO records, Vol. 9 Page 3901)

BLM resurvey by Peterson & Berry, under Group #739, Survey May/July 1971 (DCSO records, Volume 37 Page 15204) (Also, see Page 15164)

Point for the cor. of Tps. 25 and 26 S., Rs. 7 & 8 W., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long 2½" dia., 22" in the ground, with brass cap mkd.

T 25 S
R 8 W R 7 W
S 36 | S 31
S 1 | S 6
T 26 S

1971 from which

- A Fir 10" dia., bears N.22°E., 87 lks. dist. mkd. T25S R7W S31 BT.
- A Fir 15" dia., bears S.49°E., 44 lks. dist., mkd. T26S R7W S6 BT.
- A Fir 20" dia., bears S.14°W., 52 lks. dist., mkd. T26S R8W S1 BT.
- A Fir 10" dia., bears N.45°W., 23 lks. dist., mkd. T25S R8W S36 BT.

Found OK by M. Heimburger, June 1998 - M130-3

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 3/7/2000 - C.S. File 66/14-38

Found - 1971 BLM BC/IP, protrudes 8" above ground. 10" now 11" dia., 7' high rotted D.Fir snag with a partially healed single blaze illegible scribing visible, Rec. N.22°E., 57.4 ft. not measured. continued next page

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION Tsp. Cor. SW Cor. Section 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

15" now 18" dia., 1½' high D.Fir stump with a fully healed blaze, bears S.49°E., 29.0 ft.
10" now 18" dia., D.Fir with a fully healed single blaze bears N.45°W., 15.2 ft.
20" now 34" dia., D.Fir with a fully healed single blaze bears S.14°W., 34.3 ft.
New BTs- 8" D.Fir Double blazed and scribed "T25S R7W S31 CS BT" bears N.34½°E., 18.0 ft.
8" D.Fir double blazed & scribed "T26S R7W S6 CS BT" S.39°E., 14.5 ft.

Found OK by K. Hoffine, Aug. 2003 - M143-4