

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 30; & 25 of T. 25-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Original - W.H. Byars, under Contract #202, dated Mar. 11, 1874 (DCSO records, Volume 9 Page 3890)</p> <p>-----</p> <p>Set Cedar post for ¼ sec. cor., from which A Laurel 10" dia., bears N.82°E., 36 lks. dist. A Laurel 24" dia., bears N.32°W., 33 lks. dist.</p>
<p>A.R. &amp; S.C. Flint, GLO survey, 1881, found post &amp; BTs. (DCSO records, Vol. 9 Page 3897)</p>
<p>BLM resurvey by Beck &amp; Jelley, Group #563, Survey 1964 (DCSO records, Volume 33 Page 13740)</p> <p>-----</p> <p>Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner. Set a Iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 1 ft. base to top, with brass cap mkd:</p> <p style="text-align: center;">T 25 S R 8 W ¼ R 7 W S 25   S 30 1964</p> <p>from which A Fir 8" dia., bears N.76°E., 11 lks., mkd. ¼ S30 BT.</p>
<p>Ronald Geisler, LS 1988 - For: Champian International Corp. - April/June 1983 - M 94-31</p> <p>-----</p> <p>1/4 Cor. Secs. 25 &amp; 30 T25-7 Found - 1964 BLM BCIP &amp; the following accessories: 18" Fir, bears S.34°W., 8.5' (no record found) 13" Fir, bears N.70°E., 6.4' (rec. = N.76°E., 7.3') Both BTs have closed faces.</p>
<p>Fd. BC by J Terrel 6/2024 - M185-12</p>
<p> </p>