

PRIMARY CORNER DESCRIPTION CC Cor. for 18 & 19 only (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Wm. P. Heydon, Contract #656 dated May 21, 1896
(DCSO records, Volume 9 Page 3917)

Intersect W. bdy. of the Tp. 12.76 chs. S. of the cor. to
secs. 13, 18, 19, and 24, where I set, Fir post, 3 ft. long
4" sq. 24" in the ground, for closing corner of secs. 18 & 19
marked C C T25S R7W on E.; S18 on N.; S19 on S.; faces with 3
grooves on N and S faces, from which

A Fir 24" dia., bears N.69°E., 38 lks. dist. mkd. "CC
T25S R7W S18 BT".

A Laurel 18" dia., bears S.35°E., 48 lks. dist., mkd.
"CC T25S R7W S19 BT."

BLM resurvey by Beck & Jelley - Group #563 - Survey, 1964
(DCSO records, Volume 33 Pages 13755-56)

Intersect the E. bdy. of T25S R8W, and true point for the
closing corner of secs. 18 and 19, T25S R7W.

Set a Iron post, 28" long, 2½" diam., 24" in the ground, with
brass cap mkd:

T 25 S	
R 8 W	R 7 W
	S 18
S 24	S 19 CC
1964	

from which

A Cedar 20" dia., bears N.38½°E., 137 lks. mkd. T25S R7W
S18 CC BT.

A W.Fir 9" dia., bears S.33½°E., 65 lks. mkd. T25S R7W
S19 CC BT.

From this point, the orig. closing corner of secs. 18 & 19
bears N.89°42'W., 0.52 chs. perpetuated with an I.P. 1" dia.,
protruding 6" above the ground, firmly set, from which the
original bearing trees:

A Fir 38" dia., bears N.69°E., 48 lks., with scribe marks
CC BT visible on double bark blaze. (Rec. 38 lks.)

A Madrone 27" dia., bears S.35°E., 38 lks. with a
partially healed blaze. (Rec. 48 lks.)

Kris DeGroot - For: Roseburg Resources - 2/2002 - M 137-49

Found - 1964 BLM BCIP, firmly set, projecting 3" above the
ground, (properly mkd.)

From which BTs by Beck & Jelley in 1964:

23" Cedar bears N.41½°E., 90.4 ft. with a healed
blaze (rec. N.38½°E.)

20" W.Fir bears S.32°E., 42.4 ft. with a healed
blaze (rec. S.33½°E., 65 lks)

continued next page

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION CC Cor. for 18 & 19 only (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

1" Iron pipe at orig. closing corner now missing.
And a BT by Smalley in 2001:
13" W.Fir bears N.63½°E., 14.6 ft. scribed "S18 BT"
with a brass washer stamped "LS 2354"

Note - By agreement, new BTs at this corner was scribed by Mark Smalley PLS 2354 of Roseburg Resources, are being entered into the Douglas County Surveyors records by this survey, in lieu of separate corner reports being filed by Smalley on these corners.