

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 18 only (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - BLM survey by Beck & Jelley, Group #563. Survey, 1964 (DCSO records, Volume 33 Page 13743)

Point for the 1/4 sec. cor. of sec. 18 only, T25S R7W, at proportionate distance latitudinally, on the W. bdy. of sec. 18.

Set a Iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd:

|T 25 S
|R 7 W
|1/4 S 18
1964

from which

A Fir 28" dia., bears N.50°E., 47 lks., mkd. 1/4 S18 BT.

A W.Fir 15" dia. bears S.49°E., 41 1/2 lks. mkd. 1/4 S18 BT.

Found - 1964 BLM BCIP, firmly set, projecting 3" above the ground, (properly mkd.)

From which BTs by Beck & Jelley in 1964:

30" W.Fir bears S.49°E. 27.4 ft. with a healed face.

New BT - 26" D.Fir bears N.42°E., 39.8 ft. scribed "1/4 S18 BT"
(Double blazed face with a brass washer stamped "PLS 1941" nailed into the lower blaze. Bearing is taken to the center of the tree at the root crown and the distance is measured to a nail in the root crown at the side & center of the tree. Red band painted around the tree & the blazed face painted red & BT sign nail to tree.)