

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION WC Sec. Cor. 6 & 7; 1 & 12 of T.25-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Deputy, Contract #73 dated June 8, 1857 (DCSO records, Vol. 9 Page 3873)

Intersect left bank of Umpqua River and set post corner secs. 6, 7, 1 & 12, from which

- A Fir 12" dia., bears N.42°E., 87 lks.
- A Fir 9" dia., bears N.7°E., 60 lks.
- A Laurel 10" dia., bears N.15°W., 65 lks.
- An Oak 12" dia., bears N.45°W., 44 lks.
- No bearing trees convenient south of corner.

BLM resurvey by James Jelley, Group #563 - Survey, 1964 (DCSO records, Volume 33 Page 13747)

Point for the witness corner to the cor. of secs. 1, 6, 7 and 12. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

T 25 S
R 8 W R 7 W
S 1 S 6
S 12 S 7
WC
↓
1964

from which

- A Fir 14" dia., bears N.43½°E., 94 lks. mkd. X BT.
- A boulder, 8 x 4 x 4 ft. above ground, bears S.27°E., 30 lks., mkd. X BO
- A Fir 8" dia., bears S.31¾°W., 60 lks. mkd. X BT.
- A boulder 3 x 2 x 2 ft. above ground bears N.47°W., 13 lks., mkd. X BO.

Ronald Geisler, LS #1988, For: Champion International - Feb. thru March 1983 - RM 93-79

Found - 3" BLM Brass cap on a 2½" I.P. set in 1964, on the North bank of Umpqua River.

- 14" Fir bears N.43½°E., 62.0 ft., closed face (1964)
- Chiseled X BO on an 8' x 4' x 4' boulder bears S.27°E., 19.8 ft. (1964)
- Chiseled X BO on a 3' x 2' x 2' boulder bears N.47°W., 8.6 ft. (1964)

Set Chiseled X on a 4' x 3' x 2' boulder bears S.15½°W., 18.7'.

Fd. ok by K. DeGroot, 3/2001 - M132-79