

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 100639

PRIMARY CORNER DESCRIPTION WC 1/4 Cor. for Secs. 6; & 1 of T. 25-8

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Original - Dennis Hathorn, Deputy, Contract #73 dated June 8, 1857 (DCSO records, Vol. 9 Page 3873)

Set qr. sec. post and built stone mound in edge of same creek, from which

A Maple 12" dia., bears N.2°W., 322 lks.

A Myrtle 20" dia., bears N.40°E., 25 lks

GLO retracement by A.R. & S.C. Flint, Contract #392 dated, 1881, found post w/stone mound & witness trees. (DCSO Vol. 9 Page 3898)

BLM resurvey by James Jelley, Group #563 - Survey 1964 (DCSO records, Volume 33 Page 13748)

Point for the witness cor. to the ¼ sec. cor. of secs. 1 and 6. Set an iron post, 28" long, 2½" dia., 24" in the ground with brass cap mkd.

T 25 S

R 8 W R 7 W

WC

↑

¼

S 1 | S 6

1964

from which

A Fir 79" dia., bears N.61°E., 156 lks. mkd. X BT.

A Fir 32" dia., bears S.47°W., 261 lks. mkd. X BT.

(Note: Continuing N.0°13'W., .83 chs.; True point for the ¼ sec. cor. of secs. 1 & 6, at proportionate dist; there is no remaining evidence of the original corner. The cor. point falls in Little Wolf Creek, 20 lks. wide, from S.60°W., course N., where it is impractical to establish a permanent monument.)

BLM rehabilitation of certain corners, Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech., under Group #2000, Surveyed June 2003, - (DCSO records Vol. 54 Page(s) 21231)

The witness cor. to the ¼ sec. cor. of secs. 1 & 6, on the E bdy. of the Tp., monumented with an iron post, 2½" dia. firmly set, projecting 6" above ground, with brass cap (properly) mkd from which the remains of BTs mkd. by Beck and Jelley

A fir snag, 79" dia., bears N.61¾°E., 102.4 ft., with a healed blaze. (Record, N.61°E., 103.0 ft.)

A fir snag, 33" dia., bears S.46¾°W., 171.9 ft., with no marks visible. (Rec S.47°W. 172.3 ft.) cont next pg

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 100639

PRIMARY CORNER DESCRIPTION WC 1/4 Cor. for Secs. 6; & 1 of T.25-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and new bearing trees
A fir, 16" dia., bears N.76 $\frac{3}{4}$ °E., 84.6 ft., mkd. X BT.
A fir, 25" dia., bears N.78 $\frac{1}{4}$ °W., 154.7 ft., mkd. X BT.
Each new bearing tree has a 2 $\frac{1}{2}$ "x $\frac{1}{4}$ " magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description
The geographic position (NAD 1983) of this cor., as determined by a differentially corrected, mapping grade GPS receiver (Trimble GEO Explorer 3) observation, is as follows:
Latitude: 43°25'31.2" N.; Longitude: 123°35'07.2"W.