

PRIMARY CORNER DESCRIPTION Tsp. Cor. NW Cor. Section 6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Deputy, Contract #73 dated June 8, 1857 (DCSO records, Vol. 8 Page 3194)

Set post, cor. Tps., 24, 25 S., R 7 and 8 W., from which
A Fir 60" dia., bears S.60°W., 13 lks. dist.
A Fir 15" dia., bears S.40°E., 88 lks. dist.
A Chinquapin, 12" dia., bears N.52°E., 39 lks. dist.
An Alder 12" dia., bears N.65°W., 45 lks. dist.

GLO survey, Exteriors of T.24S., R8W. by W.H. Byars, under Contract #292 dated Aug. 7, 1878 (DCSO records, Volume 8 Pages 3293-94)

I re-establish the SW cor. to T.24S R7W. Find S and W bdy. lines of Tp. and at their point of intersection, which is on a recent slide, set compass, from which
A Fir 20 (15) ins. diam., bears S.40°E., 88 lks. dist.
A Fir 60 ins. diam. This tree has been carried about 2 chs. down the mountain and is lying down.
An Alder 12" dia., bears N.65°W., 45 lks. dist. We find a stump here but tree is gone.
A Chinquapin 12" dia., bears N.52°E., is carried away with the slide and entirely destroyed.
Set a pitchy Fir limb, 3 ft. long, 5" dia., 20" in ground, for the cor.

GLO survey by Harold Corbin, under Group #'s 350 & 427. Survey June/July 1959 (DCSO records, Vol. 30 Pgs. 12610-11)

The original cor. of Tps. 24 and 25 S., Rs. 7 & 8 W., determined at record bearing and distance from the only remaining original bearing tree:
A sawed Fir stump 36" dia., bears S.40°E., 88 lks. dist., with scribe marks BT and other illegible scribe marks visible on partially opened blaze.
At the corner point, Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:
T 24 S
R 8 W R 7 W
S 36 | S 31
S 1 | S 6
T 25 S
1959

Cont. Next page

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION Tsp. Cor. NW Cor. Sec. 6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which

A Hemlock 12" dia., bears N.47°E., 36 lks. dist., mkd.
T24S R7W S31 BT.

A Hemlock 13" dia., bears S.74°E., 22 lks. dist.,
mkd. T25S R7W S6 BT.

A Fir 9" dia., bears S.40½°W., 60 lks. dist.,
mkd. T25S R8W S1 BT.

An Alder 9" dia., bears N.71°W., 44 lks. dist., mkd.
T24S R8W S36 BT.

Found OK, Howard Johnstone, May 1987, M 104-16 & M104-55

BLM resurvey by Jelly; Wofford; & Rogers, Group #'s 926 & 958
(DCSO records, Volume 42 Pages 16429-30) Found 1959 Brass cap
and five BTs.