

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 31; & 6 of T26-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Dennis Hathorn, under Contract #57 dated April 1855 (DCSO records, Volume 9 Pages 3857-58)

-----  
Set ¼ sec. post, from which  
    A Fir 8" dia., bears N.65°W., 8 lks.  
    A Cedar 36" dia., bears S.45°W., 9 lks.

-----  
GLO survey by A.R. and S.C. Flint, under Contract #392 dated May, 1881 (DCSO records, Volume 9 Page 3901)

-----  
Found old post, decayed and down, also found witness trees, made and set a Fir post, 3 ft. long, 4" sq., from which  
    A Fir 8" dia., bears N.65°W., 8 lks. dist.  
    A Cedar 36" dia., bears S.45°W., 9 lks. dist.

-----  
Bureau of Land management resurvey by Peterson; Berry; etal; under Group #'s 744 & 838. Survey May 1971/Aug. 1974. (DCSO records, Volume 37 Page 15163)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an Iron post, 28" long 2½" dia., 24" in the ground, with brass cap mkd:    T 25 S R 7 W  
                            1/4    S 31  
                                      S 6  
                                    T 26 S  
                                    1971

from which  
    A Fir 10" dia., bears N.41°W., 35 lks. dist., mkd. ¼ S31 BT.  
    A Fir 15" dia., bears S.30°W., 24 lks. dist., mkd. ¼ S6 BT.

-----  
Burton W. Holt, L.S. #418. For: Sun Studs - May 13, 1985  
C.S. File 63/8-12

-----  
Found - 1971 BLM brass cap.  
    20" Fir bears S.30°W., 16.2 ft.  
This area was to be logged in 1984 so I removed the pipe and cap and replaced with a 5/8" x 30" iron rod set deep in the ground in the exact position of the pipe and BC. After the logging and slash burning, I RESET the pipe and BC in its  
(Cont. Next Page)

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31; & 6 of T26-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

original position putting it directly over the iron rod.  
New Accessory:

The orig. BT is now a 20" Fir stump 7 ft. tall. I  
rescribed the tree "1/4 S BT" and nailed a  
bearing tree tag on west side facing road.  
Corner is on a landing 50 ft. East of road. No other tree  
available.

Kristian DeGroot - surveyed for Jerry Lamb, June 1994 M119-33  
-----

Found - 2" iron pipe with a 3 1/4" USBLM brass cap by Popken in  
1975, firmly set projecting 6" above ground,  
properly marked from which:  
18" high stumped D.Fir bears S.30°W., 16.2 ft. with  
scribe marks "1/4 S6 BT" visible.

New BTs -  
11" W.Fir bears S.75°W., 80.3 ft. scribed "1/4 S6 BT"  
18" D.Fir bears S.2°W., 118.6 ft. scribed "1/4 S6 BT"