

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for ses. 19 and 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W. H. Byars, under Contract #202 dated March 11, 1874 (DCSO records, Volume 9 Page 3895)

Marked Fir, 16" dia., for ¼ sec. cor., from which
A Fir 8" dia., bears N.40°E., 7 lks. dist.
A Fir 6" dia., bears S.80°E., 57 lks. dist.

BLM resurvey by Jelley, under Group #563, survey, 1964 (DCSO records, Volume 33 Pages 13751-52)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set a Iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd: T 25 S R 7 W

¼ $\frac{S\ 19}{S\ 30}$
1964

from which
A Hemlock 17" dia., bears N.46¾°E., 69 lks. dist.,
mkd. ¼ S19 BT.
A Fir 48" dia., bears S.44°W., 61 lks. dist.,
mkd. ¼ S30 BT.