

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 18 and 19

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

Original - Wm. P. Heydon, under Contract #656 dated May 21, 1896 (DCSO records, Volume 9 Page 3918)

-----  
Set a Fir post 3 ft. long, 4" sq., 24" in the ground for 1/4 sec. cor. mkd. 1/4S on N. face, from which  
A Fir 16" dia., bears N.13°W., 27 lks. dist. mkd. 1/4S BT.  
A Fir 20" dia., bears S.59°W., 33 lks. dist. mkd. 1/4 S BT.

BLM resurvey, by Jelley, under Group #563 Survey, 1964 (DCSO records, Volume 33 Pages 13754-55)

-----  
The 1/4 sec. cor., determined at record bearing and distance from the original bearing trees:

A Fir 28" dia., bears N.13°W., 27 lks. with fragmentary scribe marks visible on opened blaze, with scribe marks BT visible on bark blaze.

A down Fir 30" dia., bears S.59°W., 33 lks. with a healed blaze.

At the corner point

Set a Iron post, 28" long, 2 1/2" diam., 24" in the ground, with brass cap mkd: T 25 S R 7 W

1/4  $\frac{S 18}{S 19}$

1964

from which a new bearing tree

A Fir 10" dia., bears S.10°W., 101 1/2 lks. mkd. 1/4 S19 BT.

Kris DeGroot - For: Roseburg Resources - 2/2002 - M 137-49

-----  
Found - 1964 BLM BCIP, firmly set, projecting 3" above the ground, stamped: T25S R7W

$\frac{S 18}{S 19}$

S 19

1964

from which an orig. BT:

24" D.Fir "high stump" bears N.10°W., 18.1 ft. w/a scribe mark "T" visible (rec. N.13°W., 27 lks)

and an orig. BT by Jelley in 1964:

10" rotted Fir stump bears S.11°W., 67.0 ft. (rec. S.10°W., 67.0 ft.)

and BTs by Smalley in 2001"

9" D.Fir bears S.60°E., 4.3 ft. scribed "1/4 S BT" w/ brass washer stamped "LS 2354"

11" D.Fir bears S.49°W., 21.4 ft. scribed "1/4 S BT" w/brass washer stamped "LS 2354"

8" D.Fir bears S.68°W., 12.9 ft. scribed "1/4 S BT" w/brass washer stamped "LS 2354"

continued next page

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 18 and 19

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

10" D.Fir bears N.52°W., 17.4 ft. scribed "¼ S BT"  
w/brass washer stamped "LS 2354"  
Note - By agreement, new BTs at this corner was scribed by  
Mark Smalley PLS 2354 of Roseburg Resources, are  
being entered into the Douglas County Surveyors  
records by this survey, in lieu of separate  
corner reports being filed by Smalley on these  
corners.