

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 31 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under Contract #202 dated March 11, 1874 (DCSO records, Volume 9 page 3892)

Set Fir post for ¼ sec. cor., from which
A Hemlock 30" dia., bears S.67°E., 35 lks. dist.
A Fir 10" dia., bears S.34°W., 31 lks. dist.

BLM resurvey by G. Steven Popken, under Group #869 - Survey, May/July 1975 (DCSO records, Vol 37 Page 15307)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set a Iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd: T 25 S R 7 W
1/4
S 31|S 32
1975

from which
A Fir 25" dia., bears N.73½°E., 41½ lks. dist.,
mkd. 1/4 S32 BT.
A Fir 16" dia., bears N.42°W., 33 lks. dist.,
mkd. 1/4 S31 BT.

Fd. OK, June 1994 by DeGroot - M119-33