

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W. H. Byars, under Contract #202 dated March 11, 1874 (DCSO records, Volume 9 Page 3894)

Set Fir post for cor. to secs. 19, 20, 29 and 30, from which
A Cedar 20" dia., bears N.29°E., 16 lks. dist.
A Fir 12" dia., bears S.25°E., 54 lks. dist.
A Fir 12" dia., bears S.11°W., 45 lks. dist.
A Fir 16" dia., bears N.41°W., 49 lks. dist.

BLM resurvey by Jelley, under Group #563, Survey, 1964 (DCSO records, Volume 33 Page 13750)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set a Iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd: T 25 S R 7 W

S 19	S 20
S 30	S 29
1964	

from which

A Fir 8" dia., bears N.31¾°E., 47 lks. dist., mkd. T25S R7W S20 BT.

A Fir 7" dia., bears S.75°E., 139 lks. dist., mkd. T25S R7W S29 BT.

A Fir 20" dia., bears S.23°W., 47 lks. dist., mkd. T25S R7W S30 BT.

A Fir 10" dia., bears N.30½°W., 39 lks. dist., mkd. T25S R7W S19 BT.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 3/8/2000 - C.S. File 66/14-40

Found OK

Note: Bearing on NE BT should be N.21 3/4°E., not N.31 3/4°E.
BT tag bearing "S.21 3/4°W."

Fd. Ok by D. Edwards, March 2010 - 2010-0032 A&B

Fd. Ok by C. Sweeden, 11/2014 - M168-68