

PRIMARY CORNER DESCRIPTION Sec. cor. for 7, 8, 17 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Wm. P. Heydon, under Contract #656 dated May 21, 1896 (DCSO records, Volume 9 Page 3912-13)

Intersect sectional correction line 106 lks. W. of cor. of secs. 7, 8, 17 and 18, heretofore described, (See Page 3910) this being out of limits and being satisfied that the error in measurement is in the latitudinal sec. line N of this at point of intersection, set CC cor. for secs. 7 and 8 to wit: A Fir post, 3 ft. long, 4" sq. 24" in the ground for closing cor. of secs. 7 and 8 mkd. CC T25S R7W on N., S8 on E. and S7 on W. faces with 5 grooves on E. and 4 grooves on S. faces from which

A Maple 18" dia., bears N.85°W., 24 lks. dist. mkd.
CC T25S R7W S7 BT.

A dogwood 6" dia., bears N.28°E., 65 lks. dist., mkd.
CC T25S R7W S8 BT.

Obliterate markings on the cor. for secs. 7, 8, 17 and 18, referring to these sections.

GLO survey by Wm. P. Heydon, under Contract #656 dated May 21, 1896 (DCSO records, Volume 9 Page 3916)

I therefore mark the closing cor. for secs. 7 and 8 as follows: T 25 S R 7 W on S., S17 on E., S18 on W. faces, from which

A Chinquapin 8" dia., bears S.51°W., 46 lks. mkd. T25S
R7W S18 BT.

A Myrtle 6" dia., bears S.54°E., 51 lks., mkd. T25S R7W
S17 BT.

I erase all marks on objective cor. post and bearing trees referring to secs. 17 and 18.

BLM resurvey by Jelley, under Group #563 - Survey, 1964 (DCSO records, Volume 33 Pages 13756-57)

The cor. of secs. 7, 8, 17 and 18 determined at record bearing and distance from the remaining original BTs:

A Myrtle 6" dia., bears S.54°E., 51 lks., with illegible scribe marks visible on opened blaze.

A down and rotted Chinquapin 14" dia., bears S.51°W., 46" lks., no marks remaining.

and a bearing tree of which I have no record:

A Fir 50" dia., bears N.52°E., 44½ lks. dist., with scribe marks T25S and other illegible marks visible on opened blaze.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. cor. for 7, 8, 17 and 18

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

At the corner point
 Set a Iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the
 ground, with brass cap mkd: T 25 S R 7 W

S 7	S 8
S 18	S 17
1964	

from which new bearing trees
 A W.Fir 10" dia., bears S.24½°E., 83 lks., mkd. T25S R7W
 S17 BT.
 A W.Fir 20" dia., bears S.70°W., 27½ lks., mkd. T25S R7W
 S18 BT.
 A W.Fir 27" dia., bears N.74°W., 69½ lks., mkd. T25S R7W
 S7 BT.
 Fd. Brass cap, Dec. 1992, Mark Heimbürger, M 112-64
 Fd. Brass Cap, Sept. 15, 1993, Mark Heimbürger, M 117-59

Kris DeGroot - For: Silver Butte Timber Co. - Dec. 2014 -
 M168-74

 Found - A 2½"x28" iron post by Jelley, in 1964 with a
 properly mkd 3¼" brass cap. The iron post
 leaning and fully exposed from base to top on
 the uphill edge of the root hole of an
 uprooted 42" D.Fir with the flanged base
 setting on a solid pitched root 36" above the
 bottom of the root hole. The flanged base of
 iron post was in its original position as
 monumented by jelley in 1964. I referenced the
 position of the base of the iron post and
 removed the existing roots that it was setting
 on and then reset the iron post 20" in the
 ground in the root hole.

From which an original BT:
 A 18" Myrtle bears S.51½°E., 32.8 ft with the face
 and center of the tree completely rotted away.
 (Rec. S.54'E., 51 LKS.)

And bearing trees by Jelly in 1964:
 A 52" D.Fir bears N.52°E., 27.2 ft with healed
 blaze. (Rec. 44½ lks.)
 A 15" W.Fir bears S.24°E., 54.3 ft with a healed
 blaze. (Rec. S.24½°E., 83 lks.)
 A 31" W.Fir bears S.68½°W., 18.7 ft with a healed
 blaze. (Rec. S.70°W., 27½ lks.)
 A 33" W.Fir bears N.74°W., 44.8 ft with a healed
 blaze. (Rec. 69½ lks.)