

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 200626

PRIMARY CORNER DESCRIPTION Meander Cor. Between Secs. 5 & 6

Alias 861460 Description Right bank of Umpqua River
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Deputy, Contract #73 dated June 8, 1857 (DCSO records, Vol. 9 Page 3884)

Marked a Fir 24" dia., on right bank for Meander cor.
A fir, 40" dia., bears West 10 lks.
A Fir, 12" dia., bears S.10°E., 25 lks.

BLM dependent resurvey by Bryan S. Seibold & Wayne Rogers, Cadastral Surveyors, under Group #1862, surveyed Sept.-Dec. 1997 - (DCSO records Vol. 53 Page(s) 20308-9)

Point for the meander cor. of secs. 5 & 6, on the right bank of the Umpqua River, at proportionate distance between the cor. of secs. 5, 6, 7 and 8 and the point established by Ronald G. Geisler, in 1983, recorded in the Douglas County Surveyor's Office map file, M93-79, as the true point for the 1/4 sec. cor. of secs. 5 & 6, within the meanders of the Umpqua River; there is no remaining evidence of the original cor.

Set a stainless steel post, 28" long, 2½" diam., 26" in the ground, with brass cap mkd.

MC
S 6 | S 5
T 25 S R 7 W
1997

from which

The middle trunk of a triple trunk myrtle, 27" diam., bears N.42 3/4°E., 42½ lks. mkd. T25S R7W S5 MC BT.

An ash, 18" diam., bears N.73°E., 13 lks., mkd. "X" BT.
Deposit a magnet in a white plastic case at the base of the stainless steel post.