

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H.Byars, under Contract #202 dated March 11, 1874 (DCSO records, Volume 9 Page 3893)

Marked Fir bush 4" dia., for 1/4 cor., from which
A Laurel 8" dia., bears North, 18 lks. dist.
A Laurel 8" dia., bears S.12°E., 25 lks. dist.

G. G. Stewart, Deputy - H.F. Roeder; N.E. Richardson; Frank Garnel; Otto Moore - Nov. 14, 1921 - Vol. 3 Page 100
C.S. File 2/23; Field Book 35 Pg. 44

Found - 6" Laurel, ant eaten and dying. Had been scribed.
Other BT gone.
6" Fir, had been blazed for corner but no scribe marks. Marked Fir "1/4 Sec. Cor".
New BTs - 10" Fir S.7°E., 35.2 ft.
24" Fir N.86°E., 17 ft.

Doug. County Surveyors Office - John Powell; J. Heritage;
July 2, 1971 - C.S. File 54/10-20

Found - Fir corner tree, shows good scar.
24" D.Fir now 30", N.86°E., 17.0 ft. (to face) Bark scribed "1/4 S29".
10" D.Fir now 19" S.7°E., 35.2 ft. (to face) Shows good scar.
Set Brass cap on south side of 14" Corner tree, mkd:
County Surveyor's T 25 S R 7 W
Office, 1971 1/4 S 29
S 32

Reblazed and rescribed:
30" D.Fir N.86°E., 18.5 ft. scribed 1/4 S29 CS BT.

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 3/16/1998 - C.S. File 66/2-6

Found - 4" now 16 dia., D.Fir with fully healed blazes on four sides. (Orig. corner tree.)
2 1/2" dia., brass cap on a 1 1/2" O.D. iron pipe, surrounded by a mound of stone, protrudes 15" above ground bears S.30°W., 1.5 ft. from corner tree.

Bearings taken from corner tree.

8" now rotted Madrone at record bearing "North, 11.9 ft." (Evidence of old blaze) OBT

(Cont. next page)

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

8" now root hole with sprouts of young Madrones growing at record bearing "S.12°E. 16.5 ft." OBT

24" now 36" dia., D.Fir with a fully healed single blaze bears N.86°E., 18.0 ft. (Rec. N.86°E., 17.0 ft., distance goes to blaze) 1921

10" now 26" dia., D.Fir with a fully healed single blaze bears S.7°E., 34.3 ft. (Rec. S.7°E., 35.2 ft. fits well as a slope distance) 1921

New BTs- **Bearings taken from corner tree.**

5" dia. B.Oak double blazed and scribed "¼ S32 CS BT" bears S.59°W., 22.5 ft. (Note: tree is pistol butt, bearing goes to center of root crown).

4" dia. Madrone, bark scribed "¼ S29 CS BT" bears N.33½°E., 25.6 ft.

Note - See sketch in file.

Fd. Ok by D. Edwards, 8/1999 - C.S. File 65/25-6
Fd. Ok by D. Edwards, Feb. 2006 - M149-71

2