

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION North 1/4 Cor. Sec. 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W. H. Byars, under Contract #202 dated March 11, 1874 (DCSO records, Volume 9 page 3896)

Set Oak post for ¼ sec. cor., from which
 A Laurel 4" dia., bears S.49°E., 16 lks. dist.
 A Laurel 4 dia., bears N.32°W., 26 lks. dist.
On high burned ridge, course SE.

Doug. County Surveyors Office - Larry E. Monrean, Deputy - S. Flause, Alex Stephens - March 27, 1980 - C.S. File 61/6-21

CONDITION REPORT ONLY. NO REMONUMENTATION FROM OUR OFFICE.
Found - 1/2" Iron pipe protruding 14" from ground and firmly set. Origin unknown. We note BLM tags on bearing trees dated May 1978
No evidence of orig. BTs; corner may have been proportioned in.
An 11" D.Fir bears N.54½°W., 9.7 ft. (tag reads S.56°E., 9.3 ft.) marked with a single blaze 3 ft. high on tree, unhealed, unscribed and tagged with BLM BT tag.
A 13" D.Fir bears S.23°E., 11.1 ft. (tag reads N.22°W., 11.1 ft.) mkd. with a single blaze 4 ft. high on tree, unhealed, unscribed and tagged with a BLM BT tag.
(Cor. looked for, appears to be for 20 only)

Thomas E. Shrum, P.L.S. #1706, For: Champion International Dec. 13, 1982 - M 93-43

Set - 2½" alum. cap mkd. P.L.S. 1706, on a 1" x 36" I.P.
New BTs - 14.5" D.Fir bears N.73°30'W., 13.5 ft.
 14" D.Fir bears S.5°15'W., 12.5 ft.