

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Section 8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Wm. P. Heydon, under Contract #656 dated May 21, 1896 (DCSO records, Volume 9 Page 3909)

-----  
Set a Fir post, 3 ft. long, 4" sq., 24" in the ground for 1/4 sec. cor. mkd: 1/4 S on N. face, from which  
A Fir 30" dia., bears N.36°E., 50 lks. dist. mkd.  
1/4 S BT.  
A Fir 20" dia., bears N.59°W., 50 lks. dist., mkd.  
1/4 S BT.

J.W. Cole, County Surveyor - Wit: H. Streese; John Harding; Ed Mosher; Kenney Emmett - Feb.7, 1924 - Vol. 3 Page 180

-----  
I renewed this corner from an orig. BT, which was 40" dia., plainly marked & facing N.59°E.  
I set post to correspond with facing 50 lks. from tree and checked position by measurement West to creek and a blazed line passing through this position.  
I marked a bluff 1/4 S CS B.O. and set a large Maple post for corner, bluff bears S.31°E., 64.6 ft.

Doug. County Surveyors Office - Vernon Tracy; V. Perron; and Don Collins, BLM - July 27, 1970 - C.S. File 54/10-19

-----  
Found - Rock Bluff with faint marks "CS BO" as called for by Cole, which bears S.31°E., 64.6 ft, 4.0 ft. above ground.  
Orig. BT that was apparently used by Cole: 48" Fir S.45°W., 33.0 ft. (face) alive, shows "1/4 S BT" bark scribe. We rescribe "1/4 S CS BT", low and alongside old scribe. (Rec. brg. N.59°W.)  
Orig. 48" Fir snag bears N.65°E., 19.4 ft. (Rec. N.36°E., 33 ft.), badly burned and decayed on SW side. (We believe this to be other orig. BT)  
Set Brass cap at cor. mkd: County Surveyor's T 25 S R 7 W  
Office 1/4 S 8  
1970  
New BT - 8" Chinquapin S.74°E., 27.3 ft. mkd. 1/4 S8 CS BT.  
This cor. lies on very steep rocky northerly slope. Note: brass cap reset 10.0 ft. N.31°W. on this date to use Cole's record distance of 64.6 ft. from bluff.

Fd. Brass cap, Dec. 1992, M. Heimburger, M 112-64  
Fd. Brass cap, Sept. 1993, M Heimburger, M 117-59

Cont.

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 8 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Kris DeGroot - For: Silver Butte Timber Co. - Dec. 2014 - M168-74

-----

Found - A 1¼" I.P. with a properly marked 2½" brass cap by Tracy, DCSO, in 1970, leaning over and loosely set a dilapidated mound of stone.

New - I rebuild a 36"x36"X36" high mound of stone with the BCIP projecting 12" above the top to the mound of stone, with accessories per record.